



www.herculestirecommercial.com

HERCULES

STRONG GUARD® HRA

PREMIUM | REGIONAL | ALL POSITION





The Strong Guard HRA Regional All-Position brings the breadth and depth to the Strong Guard line, currently offering 11 SKUs to suit our customer's needs.

- Upgraded super tensile strength steel cord provides extra durability to the carcass and steel belts, resulting in lower heat generation while protecting the integrity of the tire casing.
- Advanced silica compound technology allows the Strong Guard HRA to have the best of both worlds by optimizing fuel efficiency and removal mileage with no sacrifice to wet grip.


HERCULES

STRONG GUARD® HRA

PREMIUM | REGIONAL | ALL POSITION



PRODUCT INNOVATIONS



A WIDE SOLID SHOULDER DESIGN promotes even wear and enhanced lateral stability.

B ZIG-ZAG GROOVE DESIGN provides outstanding handling for all-position application.

MULTI-POINT EDGED GROOVES deliver better dry and wet traction.

WAVY LATERAL SIPES provide excellent wet grip and promote even wear.



84-Month Limited Protection Policy

These Hercules Strong Guard tires have a Limited Protection Policy against defects in workmanship or material for 84 months from the date of purchase.



Workmanship & Materials

If this tire becomes unserviceable due to a flaw in workmanship or materials, we will replace it at no charge during the first 50% of tread life.



Casing Allowance & Retreads

Tires carry a casing allowance for 3 retreads.

Item #	Tire Size & Service Description	Load/Speed	Ply Rating	Min Rim Width	Max Rim Width	Tread Depth (32nds)	Weight (lbs)	Overall Diameter (in)	Section Width	Single Max Load @ Pressure	Dual Max Load @ Pressure	RPM
95329	11R22.5/14	144/142 - M	G	7.5	8.25	15.7	110.45	41.5	11	6175@105	5840@105	501
95330	11R22.5/16	146/143 - M	Н	7.5	8.25	15.7	111.55	41.5	11	6610@120	6005@120	501
95321	215/75R17.5/16	135/133 - L	Н	6	6.75	15.7	57.98	30.2	8.46	4805@123	4540@123	693
95323	225/70R19.5/14	128/126 - L	G	6	6.75	15.7	63.49	31.89	8.86	3970@110	3750@110	655
95322	235/75R17.5/16	143/141 - L	Н	6.75	7.5	16.4	66.14	31.38	9.25	6005@128	5675@128	667
95324	245/70R19.5/14	133/131 - L	G	6.75	7.5	16.4	75.4	33.03	9.65	4540@110	4300@110	633
95325	255/70R22.5/16	140/137 - L	Н	7.5	8.25	17	92.06	36.61	10.04	5510@120	5070@120	571
95326	275/70R22.5/16	148/145 - M	Н	7.5	8.25	18.3	105.6	37.72	10.83	6940@130	6395@130	555
95327	295/75R22.5/14	144/141 - M	G	8.25	9	16.4	114.24	39.92	11.61	6175@110	5675@110	521
95328.1	295/75R22.5/16	146/143 - M	Н	8.25	9	16.4	114.24	39.92	11.61	6610@120	6005@120	521













