



HERCULES TIRES®
COMMERCIAL



MEDIUM TRUCK

www.herculestirecommercial.com

HERCULES STRONG GUARD® HRD

PREMIUM | REGIONAL | DEEP ALL-POSITION



The Hercules Strong Guard HRD is a Regional Deep Tread All-position design optimized for higher-scrub applications. It is available in seven standard and low-profile 22.5 inch and 24.5 inch sizes, including 315/80R22.5.

- Upgraded super tensile strength steel cord provides extra durability to the carcass and steel belts, resulting in lower heat generation while protecting the integrity of the tire casing.
- Advanced silica compound technology allows the Strong Guard HRD to have the best of both worlds by optimizing fuel efficiency and removal mileage with no sacrifice to wet grip.

HERCULES STRONG GUARD® HRD

PREMIUM | REGIONAL | DEEP ALL-POSITION



PRODUCT INNOVATIONS



- A** **A WIDE SOLID SHOULDER DESIGN**
promoting even wear and lateral stability in regional steer axle use.
- B** **STONE EJECTOR RIBS**
which help prevent stone drilling and help preserve casings for retreading.
- C** **ZIG-ZAG LATERAL SIPING**
providing excellent wet grip and enhancing even wear.
- D** **MICRO SIPES**
on circumferential groove edges that heighten wet traction and improve even wear.



84-Month Limited Protection Policy

These Hercules Strong Guard tires have a Limited Protection Policy against defects in workmanship or material for 84 months from the date of purchase.



Workmanship & Materials

If this tire becomes unserviceable due to a flaw in workmanship or materials, we will replace it at no charge during the first 50% of tread life.



Casing Allowance & Retreads

Tires carry a casing allowance for 3 retreads.

Item #	Tire Size & Service Description	Load/Speed	Ply Rating	Min Rim Width	Max Rim Width	Tread Depth (32nds)	Weight (lbs)	Overall Diameter (in)	Section Width	Single Max Load @ Pressure	Dual Max Load @ Pressure	RPM
95334	11R22.5/14	144/142 - L	G	7.5	8.25	21.4	120.37	41.5	11	6175@105	5840@105	501
95335	11R22.5/16	146/143 - L	H	7.5	8.25	21.4	121.69	41.5	11	6610@120	6005@120	501
95336	11R24.5/14	146/143 - L	G	7.5	8.25	21.4	129.41	43.46	11	6610@105	6005@105	478
95337.2	11R24.5/16	149/146 - L	H	7.5	8.25	21.4	130.51	43.46	11	7160@120	6610@120	478
95333	285/75R24.5/14	144/141 - L	G	8.25	8.25	21.4	125.44	41.34	11.22	6175@110	5675@110	503
95331	295/75R22.5/14	144/141 - L	G	8.25	9	21.4	120.59	39.92	11.61	6175@110	5675@110	521
95332	315/80R22.5/20	161/157 - L	L	9	9.75	19.5	134.48	42.36	12.4	10200@130	9090@130	490



HERCULES TIRES
COMMERCIAL

Delivered by **STD**

www.herculestirecommercial.com

