



**HERCULES TIRES®**  
COMMERCIAL



**MEDIUM TRUCK**

[www.herculestirecommercial.com](http://www.herculestirecommercial.com)

# HERCULES STRONG GUARD® HRD

PREMIUM | REGIONAL | DEEP ALL-POSITION



The Hercules Strong Guard HRD is a Regional Deep Tread All-position design optimized for higher-scrub applications. It is available in seven standard and low-profile 22.5 inch and 24.5 inch sizes, including 315/80R22.5.

- Upgraded super tensile strength steel cord provides extra durability to the carcass and steel belts, resulting in lower heat generation while protecting the integrity of the tire casing.
- Advanced silica compound technology allows the Strong Guard HRD to have the best of both worlds by optimizing fuel efficiency and removal mileage with no sacrifice to wet grip.

# HERCULES STRONG GUARD® HRD

PREMIUM | REGIONAL | DEEP ALL-POSITION



## PRODUCT INNOVATIONS



- A** **A WIDE SOLID SHOULDER DESIGN**  
promoting even wear and lateral stability in regional steer axle use.
- B** **STONE EJECTOR RIBS**  
which help prevent stone drilling and help preserve casings for retreading.
- C** **ZIG-ZAG LATERAL SIPING**  
providing excellent wet grip and enhancing even wear.
- D** **MICRO SIPES**  
on circumferential groove edges that heighten wet traction and improve even wear.



### 84-Month Limited Protection Policy

These Hercules Strong Guard tires have a Limited Protection Policy against defects in workmanship or material for 84 months from the date of purchase.



### Workmanship & Materials

If this tire becomes unserviceable due to a flaw in workmanship or materials, we will replace it at no charge during the first 50% of tread life.



### Casing Allowance & Retreads

Tires carry a casing allowance for 3 retreads.

Item #	Tire Size & Service Description	Load/Speed	Ply Rating	Min Rim Width	Max Rim Width	Tread Depth (32nds)	Weight (lbs)	Overall Diameter (in)	Section Width	Single Max Load @ Pressure	Dual Max Load @ Pressure	RPM	Price
95334	11R22.5/14	144/142 - L	G	7.5	8.25	21.4	120.37	41.5	11	6175@105	5840@105	501	
95335	11R22.5/16	146/143 - L	H	7.5	8.25	21.4	121.69	41.5	11	6610@120	6005@120	501	
95336	11R24.5/14	146/143 - L	G	7.5	8.25	21.4	129.41	43.46	11	6610@105	6005@105	478	
95337.2	11R24.5/16	149/146 - L	H	7.5	8.25	21.4	130.51	43.46	11	7160@120	6610@120	478	
95333	285/75R24.5/14	144/141 - L	G	8.25	8.25	21.4	125.44	41.34	11.22	6175@110	5675@110	503	
95331	295/75R22.5/14	144/141 - L	G	8.25	9	21.4	120.59	39.92	11.61	6175@110	5675@110	521	
95332	315/80R22.5/20	161/157 - L	L	9	9.75	19.5	134.48	42.36	12.4	10200@130	9090@130	490	



**HERCULES TIRES**  
COMMERCIAL

Delivered by **STD**

[www.herculestirecommercial.com](http://www.herculestirecommercial.com)

