

EXTREME PERFORMANCE IS ONLY HALF THE STORY

We've rounded out the Hercules® Avalanche® winter tire series: Meet the Avalanche TT. Designed specifically for your pickup truck and cargo van consumers, this tire helps them get through winter's most extreme conditions. Thanks to its enhanced ice braking capabilities and our industry-leading Hercules Performance Promise, now there's no such thing as snowed in.

 **SNOW GRIP TECHNOLOGY**



HerculesTires.com | Avalanche® TT | Premium Light Truck | Studdable Winter

HerculesTires.com/AvalancheTT || #herculestires     



HERCULES TIRES
RIDE ON OUR STRENGTH.

6



II Avalanche® TT

FEATURES & BENEFITS

1. Zig zag circumferential grooves hold snow in the tread for ideal snow-on-snow traction.
2. Center rib tie bars create consistent feedback to the driver for a more stable feel.
3. Thin gauge, full-depth siping creates more biting edges to help grab snow and ice.
4. Narrower tread width optimizes the footprint for better winter performance.
5. Optimized void to rubber ratio promotes better handling and a quieter ride.
6. The shape of the tire profile is tuned to make smooth, even contact with the road for a quieter ride.
7. Optional stud pins provide enhanced snow and ice traction.
8. Saw-tooth features of our Snow-Grabber Grooves hold snow in the tread to provide critical traction.
9. Silica tread compound allows for optimal performance in wet conditions.

SAMPLE FITMENTS

285/45R22

- Cadillac Escalade
- Lincoln Navigator
- Chevy Tahoe
- GMC Yukon

LT245/75R17

- Chevy Silverado 2500 HD
- Ford F-250/350 Super Duty

LT225/75R16

- Ram Promaster 1500-3500
- Older Cargo Vans

LT275/70R18

- Ram 2500/3500

LT245/75R16

- Mercedes Sprinter 2500
- Chevy Cargo Vans

265/70R17

- Ford F-150
- Ram 1500
- Chevy Silverado 1500

LT265/70R18

- Chevy Silverado 2500/3500 HD

235/65R16C

- Ford Transit 150-350

LT265/60R20

- Chevy Silverado 2500
- Nissan Titan XC

ITEM #	TIRE SIZE	SERVICE DESCRIPTION	LOAD ID	SIDEWALL	MIN. RIM WIDTH	MAX. RIM WIDTH	SINGLE MAX. LOAD (LBS)	DUAL MAX. LOAD (LBS)	MAX. PSI	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH	WEIGHT	STUD SIZE	
16	01769	195/75R16C	110/108R	D	BSW	5.0	6.0	2337	2205	77	27.72	7.5	13.0	18.48	12
	01762	265/70R16	112T	STD	BSW	7.0	9.0	2469	-	44	30.59	10.7	13.0	37.62	12
	01770	235/65R16C	121/119R	E	BSW	6.5	7.5	3195	3000	85	28.23	9.4	13.0	36.96	12
	01771	LT225/75R16	115/112R	E	BSW	6.0	7.0	2680	2470	80	29.49	8.6	16.5	34.54	12
	01774	LT245/75R16	120/116R	E	BSW	6.5	8.0	3042	2778	80	30.55	9.7	16.5	39.92	12
17	01779	LT265/75R16	123/120R	E	BSW	7.0	8.0	3415	3085	80	31.77	10.4	16.5	42.46	12
	01785	LT285/75R16	126/123R	E	BSW	7.5	9.0	3750	3415	80	32.91	11.3	17.0	52.89	13
	01760	255/70R17	112T	STD	BSW	6.5	8.5	2469	-	44	31.30	10.3	13.0	40.02	12
	01763	265/70R17	115T	STD	BSW	7.0	9.0	2679	-	44	31.61	10.6	13.0	38.91	12
	01772	LT235/80R17	120/117R	E	BSW	6.0	7.5	3085	2835	80	31.97	9.1	16.5	42.36	12
18	01775	LT245/75R17	121/118R	E	BSW	6.5	7.5	3195	2910	80	31.77	9.7	16.0	45.29	12
	01773	LT245/70R17	119/116R	E	BSW	6.5	8.0	3000	2755	80	30.83	9.6	16.5	43.55	12
	01777	LT265/70R17	121/118R	E	BSW	7.0	8.5	3195	2910	80	31.89	10.7	16.5	48.80	12
	01784	LT285/70R17	121/118R	E	BSW	7.5	9.0	3195	2910	80	33.11	11.7	17.0	53.46	13
	01766	275/65R18	116T	STD	BSW	7.5	9.5	2756	-	44	32.20	10.9	12.5	44.18	12
20	01778	LT265/70R18	124/121R	E	BSW	7.0	9.0	3525	3195	80	32.95	10.7	16.5	51.28	13
	01783	LT275/70R18	125/122R	E	BSW	7.0	8.5	3640	3305	80	33.35	11.1	16.0	53.96	12
	01780	LT275/65R18	123/120R	E	BSW	7.5	9.0	3415	3085	80	32.20	10.9	16.0	51.89	12
	01765	275/60R20	115T	STD	BSW	7.5	9.5	2679	-	44	33.07	10.8	12.5	47.75	12
	01764	275/55R20	117T	XL	BSW	7.5	9.5	2833	-	50	32.01	11.0	12.5	43.74	12
22	01781	LT275/65R20	126/123R	E	BSW	7.5	9.5	3750	3415	80	34.49	10.9	16.0	57.41	13
	01776	LT265/60R20	121/118R	E	BSW	8.0	9.5	3195	2910	80	32.72	10.6	16.0	51.51	13
01767	285/45R22	114T	XL	BSW	9.0	10.5	2601	-	50	32.20	11.3	12.5	42.66	12	

HERCULES PERFORMANCE PROMISE PLAN



ROAD HAZARD



45 MILE TRIAL



WORKMANSHIP



3PMS RATED

