



HERCULES TIRES
COMMERCIAL



MEDIUM TRUCK

www.HerculesTireCommercial.com

HERCULES

STRONG GUARD[®] H-MW

MIXED SERVICE | WIDE BASE | ALL-POSITION



The new Strong Guard H-MW Premium Wide Base, Mixed Service All-Position features an aggressive multi-use tread designed for heavy haul mixed service applications.

- Featuring an improved 5% deeper tread depth at 23/32nds offering enhanced traction and tread life.
- Four steel belt construction coupled with spiral wrapping technology allows for even weight distribution throughout the contact patch, increased stability, resistance to punctures and additional retread cycles.

HERCULES

STRONG GUARD® H-MW

MIXED SERVICE | WIDE BASE | ALL-POSITION



FEATURES & BENEFITS

- A** **CUT AND CHIP RESISTANT COMPOUND**
Designed specifically to withstand the abuse brought by the rough terrain of mixed service applications.
- B** **STONE EJECTORS**
In all three grooves to protect the belts and casing from road hazards in mixed service applications.
- C** **CURB PROTECTOR**
Protects the sidewall from damage in high-scrub, short-haul applications.
- D** **PROPRIETARY TREAD DESIGN**
Large siped tread blocks provide improved handling and enhanced traction while a solid shoulder reduces block squirm to fight irregular wear.



These Hercules Strong Guard tires have a Limited Protection Policy against defects in workmanship or material for 84 months from the date of purchase.



If this tire becomes unserviceable due to a flaw in workmanship or materials, we will replace it at no charge during the first 50% of tread life.



Tires carry a casing allowance for 3 retreads.

STRONG GUARD® H-MW SPECS

Item #	Tire Size & Service Description	Load/Speed	Ply Rating	Min Rim Width	Max Rim Width	Tread Depth (32nds)	Weight (lbs)	Overall Diameter (in)	Section Width (in)	Single Max Load @ Pressure	Dual Max Load @ Pressure	RPM	Price
98375	385/65R22.5	160K	20	11.75	12.25	23	175.9	42.2	15.32	9920@130	N/A	495	
98376	425/65R22.5	165K	20	12.25	13.00	23	208.6	41.9	16.93	11340@120	N/A	472	
98377	445/65R22.5	169K	20	13.00	14.00	23	212.1	43.5	17.48	12775@130	N/A	462	



www.HerculesTireCommercial.com

