

# IRONMAN

TIRES TO TRUST

## ALL COUNTRY M/T

Entry-level Mud Terrain | All-Season



When the going gets tough, the tough demand the *Ironman All Country M/T*. Designed with detours in mind and offers outstanding off-road traction in the most adverse conditions, enhanced puncture-resistant features and excellent durability in extended off-road use. With a staggered buttress that guards against high sidewall cuts and abrasions and a groove design that protects against stone drilling, the *All Country M/T* is more than capable of delivering the extra bite and extra brawn needed to overpower the elements.

### FEATURES & BENEFITS

**Shoulder blocks** easily shovel away silt and sand and enhance off-road traction.

**Void ratio** effectively promotes self-cleaning capability in muddy conditions.



**Three-ply sidewall** protects against cutting and tearing.

**Studdable tread** for extra "bite" in severe weather applications.



Backed by our 60-month Limited Protection Policy\* covering defects in workmanship and materials.

\*Valid in the US and Canada only. See the Ironman Limited Protection Policy for complete details and exclusions.

[www.IronmanTires.com](http://www.IronmanTires.com)

# IRONMAN

TIRES TO TRUST

## ALL COUNTRY M/T

Entry-level Mud Terrain | All-Season



Item #	Tire Size	Serv. Desc.	Load Range	Sidewall	Min Rim Width (in)	Max Rim Width (in)	Single Max Load (lbs)	Dual Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)	Stud
92612	31X10.50R15	109Q	C	OWL	7.0	9.0	2270	-	50	30.75	10.55	18.0	47.44	15
92613	33X12.50R15	108Q	C	OWL	8.5	11.0	2205	-	35	32.76	12.52	19.5	63.28	15
92614	LT265/75R16	123/120Q	E	OWL	7.0	8.0	3415	3086	80	31.89	10.51	18.0	58.68	15
92615	LT285/75R16	126/123Q	E	OWL	7.5	9.0	3750	3417	80	33.07	11.26	18.0	62.66	15
92616	LT315/75R16	127/124Q	E	OWL	8.0	11.0	3860	3527	65	34.80	12.32	20.5	69.69	15
92619	LT235/80R17	120/117Q	E	BSW	6.0	7.5	3085	2833	80	32.05	9.25	18.0	49.53	15
92620	LT245/75R17	121/118Q	E	OWL	6.5	7.5	3195	2910	80	31.73	9.76	18.0	50.03	15
92621	LT265/70R17	121/118Q	E	OWL	7.0	8.5	3195	2910	80	31.89	10.71	19.5	59.26	15
92622	LT285/70R17	121/118Q	E	OWL	7.5	9.0	3195	2910	80	32.99	11.50	19.5	63.69	15
98369	LT315/70R17	121/118Q	F	BSW	8.0	11.0	3195	2910	80	34.65	12.72	20.0	75.28	15
98365	35X12.50R17	121Q	F	OWL	8.5	11.0	3195	-	80	34.76	12.52	21.0	75.88	15
98374	37X12.50R17	121Q	F	BSW	8.5	11.0	3195	-	80	36.77	12.52	21.0	78.59	15
92625	LT275/65R18	123/120Q	E	BSW	7.5	9.5	3415	3086	80	32.32	10.98	19.5	59.87	15
98366	35X12.50R18	128Q	F	BSW	8.5	11.0	3970	-	80	34.76	12.52	21.0	75.69	15
98367	33X12.50R20	119Q	F	BSW	8.5	11.0	3000	-	80	32.76	12.52	21.0	73.73	15
98368	35X12.50R20	125Q	F	BSW	8.5	11.0	3640	-	80	34.76	12.52	21.0	81.60	15
98371	37X12.50R20	128Q	F	BSW	8.5	11.0	3970	-	80	36.77	12.52	21.0	82.94	15
98372	37X13.50R20	128Q	F	BSW	8.5	11.0	3970	-	80	36.77	13.58	21.0	88.88	15
98370	35X12.50R22	121Q	F	BSW	8.5	11.0	3195	-	80	34.76	12.52	21.0	77.14	15
98373	37X13.50R22	128Q	F	BSW	8.5	11.0	3970	-	80	36.77	13.58	21.0	88.30	15
97765	40x15.50R24	128Q	E	BSW	14.0	21.0	3970	-	65	39.80	15.60	21.0	104.80	15
97766	40x15.50R26	126Q	E	BSW	14.0	21.0	3750	-	65	39.80	15.60	21.0	106.20	15

IRONMAN