



HERCULES TIRES
COMMERCIAL



MEDIUM TRUCK

www.HerculesTireCommercial.com

HERCULES

STRONG GUARD[®] H-MD

PREMIUM | MIXED-SERVICE | DRIVE



The new Strong Guard H-MD Mixed-Service Drive tire features a deep open shoulder design coupled with the latest compounds and technologies that deliver a balance of enhanced traction and handling in on and off-road conditions.

- Featuring an enhanced speed rating of "K" 68MPH to meet on-road demands.
- The 7% wider tread width, staggered gem-shaped lugs and open shoulder design provide an optimized footprint for heavy load applications both on and off-road.

HERCULES

STRONG GUARD® H-MD

PREMIUM | MIXED-SERVICE | DRIVE



FEATURES & BENEFITS



- A OPTIMIZED FOOTPRINT AND WIDE TREAD DESIGN**
Extends tread life, improves product performance and increases vehicle stability due to a larger contact patch.
- B CUT AND CHIP RESISTANT COMPOUND**
Designed specifically to withstand the abuse brought by the rough terrain of mixed service applications.
- C TCS STONE EJECTORS**
Full coverage stone ejectors with added Truncated Cone Shaped ejectors protect the tire casing from multiple angles.
- D CURB PROTECTOR**
Protects the sidewall and casing from damage in mixed-service applications.



These Hercules Strong Guard tires have a Limited Protection Policy against defects in workmanship or material for 84 months from the date of purchase.



If this tire becomes unserviceable due to a flaw in workmanship or materials, we will replace it at no charge during the first 50% of tread life.



Tires carry a casing allowance for 3 retreads.

STRONG GUARD® H-MD SPECS

ITEM #	TIRE SIZE & SERVICE DESCRIPTION	LOAD/SPEED	PLY	MIN RIM WIDTH	MAX RIM WIDTH	TREAD DEPTH (32NDS)	WEIGHT (LBS)	OVERALL DIAMETER (IN)	SECTION WIDTH	SINGLE MAX LOAD @ PRESSURE	DUAL MAX LOAD PRESSURE	RPM	PRICE
98480	11R22.5/16	148/145-K	H	7.50	8.25	32.0	133.60	41.93	10.98	6940@123	6390@123	495	
98481	11R24.5/16	149/146-K	H	7.50	8.25	32.0	142.42	43.94	10.98	7160@120	6610@120	473	
COMING SOON 98491	12R22.5/18	152/149-K	J	8.25	9.00	32.0	158.70	42.71	11.81	7830@135	7160@135	486	



www.HerculesTireCommercial.com

