



**HERCULES TIRES**  
COMMERCIAL



**MEDIUM TRUCK**

[www.HerculesTireCommercial.com](http://www.HerculesTireCommercial.com)

**HERCULES**

# STRONG GUARD<sup>®</sup> H-MX

PREMIUM | MIXED-SERVICE | DRIVE



The new Strong Guard H-MX mixed-service drive features a wide open shoulder tread pattern coupled with the latest compounds and technologies delivering x-treme traction and durability in the most severe applications.

- Featuring 7% wider tread and 10% wider belt layer, the Strong Guard H-MX is purpose built for x-treme off road conditions.
- The proprietary tread design features a lightning center groove for improved heat dissipation, allowing for an enhanced speed rating of "J" 62MPH

**HERCULES**

# STRONG GUARD® H-MX

PREMIUM | MIXED-SERVICE | DRIVE



## FEATURES & BENEFITS

- A** **CUT AND CHIP RESISTANT COMPOUND**  
Designed specifically to withstand the abuse brought by the rough terrain of mixed service applications.
- B** **TRAC-LEDGES**  
Provide unparalleled traction and mud/debris clean out in x-treme off-road conditions.
- C** **CURB PROTECTOR & STONE EJECTORS**  
Protects the sidewall and casing for damage in mixed-service application.
- D** **OPTIMIZED FOOTPRINT AND WIDE TREAD DESIGN**  
Extends tread life, improves product performance and increases vehicle stability due to a larger contact patch.



These Hercules Strong Guard tires have a Limited Protection Policy against defects in workmanship or material for 84 months from the date of purchase.



If this tire becomes unserviceable due to a flaw in workmanship or materials, we will replace it at no charge during the first 50% of tread life.



Tires carry a casing allowance for 3 retreads.

## STRONG GUARD® H-MX SPECS

ITEM #	TIRE SIZE & SERVICE DESCRIPTION	LOAD/SPEED	PLY	MIN RIM WIDTH	MAX RIM WIDTH	TREAD DEPTH (32NDS)	WEIGHT (LBS)	OVERALL DIAMETER (IN)	SECTION WIDTH	SINGLE MAX LOAD @ PRESSURE	DUAL MAX LOAD PRESSURE	RPM	PRICE
98482	11R22.5/16	146/143-J	H	7.50	8.25	30.0	140.01	41.50	10.98	6610@120	6005@120	522	
98483	11R24.5/16	149/146-J	H	7.50	8.25	30.0	150.13	43.94	10.98	7160@120	6610@120	496	



[www.HerculesTireCommercial.com](http://www.HerculesTireCommercial.com)

