

# Full Line Product Catalog 2022



## TOURING/PERFORMANCE

iMOVE® Gen3 AS .....	2-3
iMOVE® PT .....	4-5
RB-12 .....	6
RB-12 NWS .....	7

## CUV/SUV/LT

iMove® Gen2 SUV .....	8
Radial A/P .....	9
All Country® AT2 .....	10-11
All Country® CHT .....	12
All Country® HT .....	13
All Country® M/T .....	14-15

## WINTER

Polar Trax Gen2 .....	16-17
-----------------------	-------

## SPECIAL ORDER

iMove® Gen2 AS .....	18-19
GR906 .....	20-21
All Country® AT .....	22-23
RB-SUV & RB-LT .....	24-25

## PROTECTION POLICIES

Limited Protection Policy .....	26-27
All-Steel Protection Policy .....	28
Casing Protection Policy .....	29
Road Hazard Protection .....	30
Buffing Guide .....	31

## iMOVE® GEN3AS



LIMITED PROTECTION



ROAD HAZARD



- Asymmetric pattern showcases larger, stable block on the outside of the tire to enhance dry performance while increased siping and lateral slits support enhanced all-season traction.
- Enhanced tread block geometry and optimized siping placement improves grip and minimizes road noise.
- 3D multi-wave sipes provide more even contact pressure resulting in a quiet, long lasting ride.
- Offset sipes and sharp angled slits deliver biting edges to enhance snow traction.

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)						
H,V,W-Speed Rated												
98381	185/60R14 82H	STD	BSW	420 A A	5.0	6.5	1047	51	22.80	7.40	10.7	16.53
98382	185/65R15 88H	STD	BSW	420 A A	5.0	6.5	1235	51	24.40	7.40	10.7	17.92
98383	195/65R15 91H	STD	BSW	420 A A	5.5	7.0	1356	51	25.00	7.90	10.7	19.82
98384.2	205/65R15 94H	STD	BSW	420 A A	5.5	7.5	1477	51	25.50	8.20	10.7	22.13
98385	195/60R15 88H	STD	BSW	420 A A	5.5	7.0	1235	51	24.20	7.90	10.7	18.83
98386	185/55R15 82V	STD	BSW	420 A A	5.0	6.5	1047	51	23.00	7.60	10.3	16.91
98387	215/65R16 98H	STD	BSW	420 A A	6.0	7.5	1653	51	27.00	8.70	10.7	26.35
98388	205/60R16 92V	STD	BSW	420 A A	5.5	7.5	1389	51	25.70	8.20	10.3	22.07
98389	215/60R16 95V	STD	BSW	420 A A	6.0	7.5	1521	51	26.10	8.70	10.3	24.41
98390	225/60R16 98H	STD	BSW	420 A A	6.0	8.0	1653	51	26.60	9.00	10.7	24.36
98391	205/55R16 91V	STD	BSW	420 A A	5.5	7.5	1356	51	24.90	8.40	10.7	21.50
98392	215/55ZR16 97W	XL	BSW	380 A A	6.0	7.5	1609	50	25.30	8.90	10.0	24.07
98393	225/55R16 99H	XL	BSW	420 A A	6.0	8.0	1709	50	25.70	9.20	10.7	23.96
98394	205/50ZR16 91W	XL	BSW	380 A A	5.5	7.5	1356	50	24.10	8.40	10.7	21.16
98395	225/50R16 96V	XL	BSW	420 A A	6.0	8.0	1565	50	24.90	9.20	10.3	22.24
98396	205/45ZR16 87W	XL	BSW	380 A A	6.5	7.5	1201	50	23.20	8.10	10.0	17.64
98397	215/55R17 94V	STD	BSW	420 A A	6.0	7.5	1477	51	26.30	8.90	10.3	23.90
98398	225/55R17 97H	STD	BSW	420 A A	6.0	8.0	1609	51	26.80	9.20	10.7	26.06
98399	235/55R17 103V	XL	BSW	420 A A	6.5	8.5	1929	50	27.20	9.60	10.3	28.26
98400	205/50ZR17 93W	XL	BSW	380 A A	5.5	7.5	1433	50	25.10	8.40	10.3	22.35
98401	215/50R17 95V	XL	BSW	420 A A	6.0	7.5	1521	50	25.50	8.90	10.3	23.66
98402	225/50R17 94V	STD	BSW	420 A A	6.0	8.0	1477	51	25.90	9.20	10.3	24.05
98403	235/50ZR17 96W	STD	BSW	380 A A	6.5	8.5	1565	51	26.30	9.60	10.0	25.11
98404	205/45ZR17 88W	XL	BSW	380 A A	6.5	7.5	1235	50	24.30	8.10	10.0	19.49

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)						
98405	215/45ZR17 91W	XL	BSW	380 A A	7.0	8.0	1356	50	24.60	8.40	10.3	21.54
98406	225/45ZR17 94W	XL	BSW	380 A A	7.0	8.5	1477	50	25.00	8.90	10.3	22.69
98407	235/45ZR17 97W	XL	BSW	380 A A	7.5	9.0	1609	50	25.40	9.30	10.3	23.74
98408	245/45ZR17 99W	XL	BSW	380 A A	7.5	9.0	1709	50	25.70	9.60	10.3	25.04
98409	205/40ZR17 84W	XL	BSW	380 A A	7.0	8.0	1102	50	23.50	8.30	10.0	18.65
98410	245/40ZR17 95W	XL	BSW	380 A A	8.0	9.5	1521	50	24.70	9.80	10.3	24.14
98411	225/60R18 100V	STD	BSW	420 A A	6.0	8.0	1764	51	28.60	9.00	10.3	28.40
98412	235/55R18 100V	STD	BSW	420 A A	6.5	8.5	1764	51	28.10	9.60	10.3	28.84
98413	225/50ZR18 95W	STD	BSW	380 A A	6.0	8.0	1521	51	26.90	9.20	10.0	25.42
98414	235/50ZR18 97W	STD	BSW	380 A A	6.5	8.5	1609	51	27.30	9.60	10.3	28.35
98415.1	245/50ZR18 100W	STD	BSW	380 A A	7.0	8.5	1764	51	27.70	10.00	10.0	29.15
98416	225/45ZR18 91W	STD	BSW	380 A A	7.0	8.5	1356	51	25.90	8.90	10.3	23.83
98417	235/45ZR18 94W	STD	BSW	380 A A	7.5	9.0	1477	51	26.30	9.30	10.3	24.38
98418	245/45ZR18 100W	XL	BSW	380 A A	7.5	9.0	1764	50	26.70	9.60	10.3	27.51
98419	225/40ZR18 92W	XL	BSW	380 A A	7.5	9.0	1389	50	25.10	9.10	10.0	21.01
98420	235/40ZR18 95W	XL	BSW	380 A A	8.0	9.5	1521	50	25.40	9.50	10.0	21.98
98421	245/40ZR18 97W	XL	BSW	380 A A	8.0	9.5	1609	50	25.70	9.80	10.0	23.85
98422	255/35ZR18 94W	XL	BSW	380 A A	8.5	10.0	1477	50	25.00	10.20	10.0	24.87
98423	235/55R19 105V	XL	BSW	420 A A	6.5	8.5	2039	50	29.20	9.60	10.3	31.04
98424	235/50R19 103V	XL	BSW	420 A A	6.5	8.5	1929	50	28.30	9.60	10.3	32.43
98425	245/45ZR19 102W	XL	BSW	380 A A	7.5	9.0	1874	50	27.70	9.60	10.0	28.88
98426	245/40ZR19 98W	XL	BSW	380 A A	8.0	9.5	1653	50	26.70	9.80	10.0	23.96
98427	225/35ZR19 88W	XL	BSW	380 A A	7.5	9.0	1235	50	25.20	9.10	10.0	22.81
98428	235/35ZR19 91W	XL	BSW	380 A A	8.0	9.5	1356	50	25.50	9.50	10.0	23.72
98429	255/35ZR19 96W	XL	BSW	380 A A	8.5	10.0	1565	50	26.00	10.20	10.0	26.51
98430	265/30ZR19 93W	XL	BSW	380 A A	9.0	10.0	1433	50	25.30	10.70	10.0	24.76
98431	275/30ZR19 96W	XL	BSW	380 A A	9.0	10.0	1565	50	25.60	10.90	10.0	27.22
98432	245/50R20 102V	STD	BSW	420 A A	7.0	8.5	1874	51	29.70	10.00	10.3	32.34
98433	245/45ZR20 103W	XL	BSW	380 A A	7.5	9.0	1929	50	28.70	9.60	10.0	28.53
98434	255/45ZR20 105W	XL	BSW	380 A A	8.0	9.5	2039	50	29.10	10.00	10.0	32.30
98435	245/40ZR20 99W	XL	BSW	380 A A	8.0	9.5	1709	50	27.70	9.80	10.0	28.44
98436	225/35ZR20 90W	XL	BSW	380 A A	7.5	9.0	1323	50	26.20	9.10	10.0	23.04
98437.1	245/35ZR20 95W	XL	BSW	380 A A	8.0	9.5	1521	50	26.80	9.80	10.3	25.90
98438	255/35ZR20 97W	XL	BSW	380 A A	8.5	10.0	1609	50	27.00	10.20	10.0	26.96
98439	245/30ZR22 92W	XL	BSW	380 A A	8.0	9.0	1389	50	27.80	9.80	10.0	26.92

## iMOVE® PT



LIMITED PROTECTION



ROAD HAZARD



- Four wide circumferential grooves enable rapid and efficient water channeling promoting of wet grip confidence.
- Chamfered tread block allows maximum contact with the road.
- Multi-groove sipe design enhances the wet and snow traction.
- Semi-closed shoulder groove design provides efficient aquaplaning resistance while improving driving comfort.
- Innovative center rib design increases straight-line driving stability and performance handling.

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)						
T,H,V-Speed Rated												
98440	155/80R13 79T	STD	BSW	380 A A	4.0	5.0	963	44	22.80	6.20	9.6	13.60
98441	175/70R13 82T	STD	BSW	420 A A	4.5	6.0	1047	44	22.70	7.00	9.6	14.80
98442	185/70R13 86T	STD	BSW	420 A A	4.5	6.0	1168	44	23.20	7.40	9.6	17.00
98443.1	175/70R14 84T	STD	BSW	420 A A	4.5	6.0	1102	44	23.70	7.00	9.6	16.20
98444	185/70R14 88T	STD	BSW	420 A A	4.5	6.0	1235	44	24.30	7.40	10.0	17.00
98445.1	195/70R14 91T	STD	BSW	420 A A	5.0	6.5	1356	44	24.80	7.90	9.8	18.30
98446	205/70R14 95T	STD	BSW	420 A A	5.0	7.0	1521	44	25.40	8.20	10.0	19.80
98447	175/65R14 82H	STD	BSW	440 A A	5.0	6.0	1047	44	23.00	7.00	9.6	15.90
98448	185/65R14 86H	STD	BSW	440 A A	5.0	6.5	1168	44	23.50	7.40	9.6	16.90
98449	195/60R14 86H	STD	BSW	440 A A	5.5	7.0	1168	44	23.20	7.90	9.8	18.30
98450	205/70R15 96H	STD	BSW	420 A A	5.0	7.0	1565	44	26.30	8.20	10.0	22.70
98451	215/70R15 98H	STD	BSW	440 A A	5.5	7.0	1653	44	26.90	8.70	10.0	23.80
98452	225/70R15 100T	STD	BSW	440 A A	6.0	7.5	1764	44	27.40	9.00	10.0	24.30
98453	185/65R15 88H	STD	BSW	440 A A	5.0	6.5	1235	44	24.40	7.40	9.6	18.20
98454	195/65R15 91H	STD	BSW	440 A A	5.5	7.0	1356	44	25.00	7.90	9.8	19.10
98456	205/65R15 94H	STD	BSW	420 A A	5.5	7.5	1477	44	25.50	8.20	9.8	21.60
98455	215/65R15 96H	STD	BSW	440 A A	6.0	7.5	1565	44	26.00	8.70	10.0	23.70
98457	185/60R15 84H	STD	BSW	440 A A	5.0	6.5	1102	44	23.70	7.40	9.8	17.70
98458	195/60R15 88H	STD	BSW	440 A A	5.5	7.0	1235	44	24.20	7.90	9.8	18.80

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)						
98459	205/60R15 91H	STD	BSW	440 A A	5.5	7.5	1356	44	24.70	8.20	9.8	20.10
98460	215/60R15 94H	STD	BSW	440 A A	6.0	7.5	1477	44	25.20	8.70	10.0	23.20
98461	205/65R16 95H	STD	BSW	440 A A	5.5	7.5	1521	44	26.50	8.20	9.8	21.70
98462	215/65R16 98H	STD	BSW	440 A A	6.0	7.5	1653	44	27.00	8.70	10.0	23.80
98463	225/65R16 100H	STD	BSW	440 A A	6.0	8.0	1764	44	27.50	9.00	10.0	25.80
98464	235/65R16 103H	STD	BSW	440 A A	6.5	8.5	1929	44	28.00	9.40	10.0	26.80
98465	205/60R16 92H	STD	BSW	440 A A	5.5	7.5	1389	44	25.70	8.20	9.8	21.70
98466	215/60R16 95H	STD	BSW	440 A A	6.0	7.5	1521	44	26.10	8.70	10.0	22.70
98467	225/60R16 98H	STD	BSW	440 A A	6.0	8.0	1653	44	26.60	9.00	10.0	23.80
98468	235/60R16 100H	STD	BSW	440 A A	6.5	8.5	1764	44	27.10	9.40	10.0	26.80
98469	205/55R16 91V	STD	BSW	440 A A	5.5	7.5	1356	44	24.90	8.40	9.8	20.70
98470	205/50R16 87V	STD	BSW	440 A A	5.5	7.5	1201	44	24.10	8.40	9.8	20.00
98471	215/65R17 99T	STD	BSW	440 A A	6.0	7.5	1709	44	28.03	8.70	10.0	25.90
98472	225/65R17 102H	STD	BSW	440 A A	6.0	8.0	1874	44	28.50	8.90	10.0	27.20
98473	215/60R17 96H	STD	BSW	440 A A	6.0	7.5	1565	44	27.20	8.70	10.0	24.80
98474	225/60R17 99H	STD	BSW	440 A A	6.0	8.0	1709	44	27.60	9.00	10.0	25.80
98475	235/60R17 102H	STD	BSW	440 A A	6.5	8.5	1874	44	28.11	9.44	10.0	26.00
98476.1	215/55R17 94H	STD	BSW	440 A A	6.0	7.5	1477	44	26.30	8.90	10.0	22.90
98477	225/55R17 97H	STD	BSW	440 A A	6.0	8.0	1609	44	26.80	9.20	10.0	24.40
98478	235/55R17 99H	STD	BSW	440 A A	6.5	8.5	1709	44	27.20	9.60	10.0	26.10

**RB-12**

- Symmetric, five-rib tread design creates larger foot print for stability and performance.
- Slotted shoulders, moderate siping and wide grooves enhance water evacuation and help to prevent hydroplaning.
- Variable tread design reduces road noise and delivers ride comfort.
- Enhanced base tread compound promotes excellent durability and traction.
- M+S Rated.



LIMITED PROTECTION



ROAD HAZARD



Approved Rim Width (in)

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Min Rim Width (in)	Max Rim Width (in)	Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
T,H,V-Speed Rated												
91841	175/70R13 82T	STD	BSW	440 A B	4.5	6.0	1047	44	22.60	6.96	9.4	14.67
91842	175/70R14 84T	STD	BSW	440 A B	4.5	6.0	1102	44	23.70	7.01	9.8	15.17
91165	185/70R14 88T	STD	BSW	440 A B	4.5	6.0	1235	44	24.21	7.48	10.1	17.09
91169	195/70R14 91T	STD	BSW	440 A B	5.0	6.5	1356	44	24.76	7.91	10.1	19.38
91840	175/65R14 82T	STD	BSW	440 A B	5.0	6.0	1047	44	23.03	6.97	9.8	14.90
91163	185/65R14 86T	STD	BSW	440 A B	5.0	6.5	1168	44	23.50	7.40	10.1	16.77
91162	185/60R14 82H	STD	BSW	440 A B	5.0	6.5	1047	44	23.50	7.40	10.1	16.51
91171	205/70R15 96T	STD	BSW	440 A B	5.0	7.0	1565	44	26.34	8.23	10.7	22.40
91174	215/70R15 98T	STD	BSW	440 A B	5.5	7.0	1653	44	26.81	8.74	11.1	23.93
91176	225/70R15 100T	STD	BSW	440 A B	6.0	7.5	1764	44	27.44	9.17	11.1	26.21
91164	185/65R15 88T	STD	BSW	440 A B	5.0	6.5	1235	44	24.44	7.44	10.1	17.87
91168.1	195/65R15 91T	STD	BSW	440 A B	5.5	7.0	1356	44	25.08	7.87	10.1	18.70
91170	205/65R15 94T	STD	BSW	440 A B	5.5	7.5	1477	44	25.47	8.15	10.1	20.65
91167	195/60R15 88T	STD	BSW	440 A B	5.5	7.0	1235	44	24.33	7.72	10.1	18.00
91166.1	195/55R15 85V	STD	BSW	440 A B	5.5	7.0	1135	44	23.46	7.83	10.1	17.87
92513	205/65R16 95H	STD	BSW	440 A B	5.5	7.5	1521	44	26.33	8.50	10.1	20.98
91173.1	215/65R16 98T	STD	BSW	440 A B	6.0	7.5	1653	44	27.08	8.70	10.1	24.24
91172	215/60R16 95T	STD	BSW	440 A B	6.0	7.5	1301	44	26.10	8.66	10.1	23.69
91175	225/60R16 98T	STD	BSW	440 A B	6.0	8.0	1653	44	26.57	8.90	11.1	24.40
91064.1	205/55R16 91T	STD	BSW	440 A B	5.5	7.5	1356	44	25.03	8.27	10.1	20.61
92479	215/65R17 99T	STD	BSW	440 A B	6.0	7.5	1709	44	27.87	9.06	10.1	24.95
92514	225/60R17 99H	STD	BSW	440 A B	6.0	8.0	1709	44	27.52	9.29	11.1	26.54
92480	235/60R17 102H	STD	BSW	440 A B	6.5	8.5	1874	44	28.03	9.80	11.1	27.84



LIMITED PROTECTION



ROAD HAZARD

**RB-12 NWS**

- Modern tread design with classic white sidewall styling.
- Computer-optimized tread design reduces road noise for a quiet, comfortable ride.
- Square tread profile maximizes contact area and improves handling stability.
- All-season compound enhances wet traction and durability.
- Lateral shoulder slots help ensure water dispersion and promote heat dissipation.
- M+S rated.

Approved Rim Width (in)

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Min Rim Width (in)	Max Rim Width (in)	Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
S-Speed Rated												
94031.1	195/75R14 92S	STD	WSW	-	5.0	6.5	1389	44	25.51	7.70	9.6	18.52
94033	205/75R14 95S	STD	WSW	-	5.0	7.0	1521	44	26.14	8.00	9.6	22.05
94034	205/75R15 97S	STD	WSW	-	5.0	7.0	1609	44	27.13	8.20	9.6	23.15
94036	215/75R15 100S	STD	WSW	-	5.5	7.0	1764	44	27.68	8.00	9.6	23.81
94038	225/75R15 102S	STD	WSW	-	6.0	7.5	1874	44	28.31	8.80	10.2	24.91
94039	235/75R15 105S	STD	WSW	-	6.0	8.0	2039	44	28.86	9.30	10.2	27.12
94032	205/70R15 96S	STD	WSW	-	5.0	7.0	1565	44	26.34	8.20	9.6	19.84
94035	215/70R15 98S	STD	WSW	-	5.5	7.0	1653	44	26.89	8.70	9.6	22.93
94037	225/70R15 100S	STD	WSW	-	6.0	7.5	1764	44	27.44	9.00	10.2	24.91

# iMOVE GEN2 SUV



- Asymmetric tread design, with distinct outside and inside tread elements, enhances handling in wet and dry conditions.
- Wide circumferential grooves maximize water evacuation to improve wet grip and protect against hydroplaning.
- Large contact patch with continuous center rib enhances directional stability, steering response and cornering grip at highway speeds.
- Performance-centric design from shoulder to sidewall appeals to enthusiasts looking for the optimal balance of quality and performance.
- M+S Rated.



Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)						
V,W-Speed Rated												
93748	275/55R20 117V	XL	BSW	420 A A	7.5	9.5	2833	50	31.89	11.18	12.0	41.90
93749.1	265/50R20 11V	XL	BSW	420 A A	7.5	9.5	2403	50	30.47	10.91	12.0	35.76
93750	285/50R20 116V	XL	BSW	420 A A	8.0	10.0	2756	50	31.26	11.69	12.0	42.00
93751	275/45R20 110V	XL	BSW	420 A A	8.5	10.5	2337	50	29.76	10.75	12.0	37.70
93752	275/40ZR20 106W	XL	BSW	420 A A	9.0	11.0	2094	50	28.66	10.94	12.0	34.00
97862	275/45R22 112V	XL	BSW	420 A A	9.0	9.0	2469	50	31.80	10.76	12.0	42.00
93753	285/45R22 114V	XL	BSW	420 A A	9.0	10.5	2601	50	32.09	11.22	12.0	44.00
93754	305/45R22 118V	XL	BSW	420 A A	9.5	11.5	2910	50	32.80	11.93	12.0	46.30
96587	265/40R22 106V	XL	BSW	420 A A	9.0	10.5	2094	50	30.35	10.67	12.0	33.90
96588	275/40R22 108V	XL	BSW	420 A A	9.0	10.5	2208	50	30.67	10.94	12.0	36.16
93755	305/40R22 114V	XL	BSW	420 A A	10.0	12.0	2601	50	31.61	12.32	12.0	44.40
93756	265/35R22 102V	XL	BSW	420 A A	9.0	10.5	1874	50	29.33	10.67	12.0	35.20
93757	285/35R22 106V	XL	BSW	420 A A	9.5	11.0	2094	50	29.88	11.42	12.0	36.60
93758	255/30R22 95V	XL	BSW	420 A A	8.5	10.0	1521	50	28.07	10.24	12.0	29.87
93759	295/35R24 110V	XL	BSW	420 A A	10.0	11.5	2337	50	32.13	11.85	12.0	44.53
93760	305/35R24 112V	XL	BSW	420 A A	10.0	12.0	2469	50	32.44	12.32	12.0	44.80

# RADIAL A/P



- Attractive five-rib, all-season tread pattern for optimum handling and long mileage.
- Computer-aided harmonic tread block placement ensures a quiet, comfortable ride.
- Durable multi-ply body and deep tread tolerate tough conditions.
- Hybrid tread design with large, staggered lugs guarantees traction on any surface.
- Heavy siping creates hundreds of biting edges for maximum grip in all weather conditions.
- M+S Rated.



Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Single Max Load (lbs)	Dual Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)							
Q,T-Rated													
91612	LT215/85R16 115/112Q	E	BSW	-	5.5	7.0	2680	2470	80	30.39	8.50	13.9	36.53
91614	LT235/85R16 120/116Q	E	BSW	-	6.0	7.5	3042	2778	80	31.73	9.25	14.2	41.43
91613	LT225/75R16 115/112Q	E	OWL	-	6.0	7.0	2680	2470	80	29.29	8.78	13.9	41.34
95686	245/75R16 111T	STD	OWL	-	6.5	8.0	2403	-	44	30.47	9.76	11.0	34.60
91615	LT245/75R16 120/116Q	E	OWL	-	6.5	8.0	3042	2778	80	30.47	9.76	14.2	45.79
91616	LT265/75R16 123/120Q	E	OWL	-	7.0	8.0	3415	3085	80	31.65	10.51	14.9	40.75
95684	225/70R16 103T	STD	BSW	-	6.0	7.5	1929	-	44	28.43	8.98	11.0	29.60
95685	245/70R17 110T	STD	OWL	-	6.5	8.0	2337	-	44	30.55	9.76	11.0	35.40
91617	265/70R17 115T	STD	OWL	400 A B	7.0	9.0	2679	-	44	31.65	10.71	12.0	38.12
95681	235/65R17 104T	STD	OWL	-	6.5	8.5	1984	-	44	29.06	9.45	11.0	31.10
95682	245/65R17 107T	STD	OWL	-	7.0	8.5	2149	-	44	29.53	9.76	11.0	33.40

# ALL COUNTRY® AT2



- Angled tread blocks for enhanced traction on dirt and gravel roads.
- Zig Zag grooves designed specifically to provide a quieter ride.
- Four circumferential grooves designed for improved traction in wet conditions.
- Full depth sipes for improved traction in wet and snow conditions.

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Single Max Load (lbs)	Dual Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)							
T,R,S-Speed Rated													
07580	235/75R15 109T	XL	BSW	500 A B	6.0	8.0	2271	-	50	28.62	9.30	11.0	29.46
07638	LT235/75R15 104/101R	C	BSW	-	6.0	7.0	1985	1820	50	28.86	9.30	14.0	32.07
07642	31X10.50R15 109R	C	BSW	-	7.0	9.0	2270	-	50	30.51	10.60	14.0	37.87
07654	LT265/75R16 123/120R	E	BSW	-	7.0	8.0	3415	3085	80	31.65	10.50	14.0	42.24
07666	LT235/85R16 120/116R	E	BSW	-	6.0	7.5	3042	2778	80	31.73	9.30	14.0	38.50
07658	LT285/75R16 126/123R	E	BSW	-	7.5	9.0	3750	3415	80	31.65	10.50	14.0	53.46
07584	235/70R16 106T	STD	BSW	500 A B	6.0	8.0	2094	-	44	28.74	9.40	11.0	28.71
07588	255/70R16 111T	STD	BSW	500 A B	6.5	8.5	2403	-	44	29.80	10.30	10.5	32.54
07592	265/70R16 112T	STD	BSW	500 A B	7.0	9.0	2469	-	44	30.24	10.80	11.0	34.03
07596	245/75R16 111T	STD	BSW	500 A B	6.5	8.0	2403	-	44	30.20	9.80	11.0	31.44
07600	265/75R16 116T	STD	BSW	500 A B	7.0	9.0	2756	-	44	31.34	10.60	11.0	34.96
07662	LT215/85R16 115/112R	E	BSW	-	5.5	7.0	2680	2470	80	30.20	8.30	13.5	34.54
07650	LT245/75R16 120/116R	E	BSW	-	6.5	8.0	3042	2778	80	30.47	9.80	14.0	36.09
07646	LT225/75R16 115/112R	E	BSW	-	6.0	7.0	2680	2470	80	29.29	8.80	14.0	33.92
07682	LT245/75R17 121/118S	E	BSW	-	6.5	7.5	3195	2910	80	31.50	9.80	14.0	42.70
07670	LT245/70R17 119/116S	E	BSW	-	6.5	8.0	3000	2755	80	30.55	9.80	14.0	40.04
07674	LT265/70R17 121/118R	E	BSW	-	7.0	8.5	3195	2910	80	31.65	10.70	14.0	44.44
07686	LT235/80R17 120/117R	E	BSW	-	6.0	7.5	3085	2835	80	31.81	9.30	14.0	38.06
07608	265/65R17 112T	STD	BSW	500 A B	7.5	9.5	2469	-	44	30.39	10.60	10.5	34.45
07604	245/65R17 107T	STD	BSW	500 A B	7.0	8.5	2149	-	44	29.49	9.60	11.0	30.14
07616	265/70R17 115T	STD	BSW	500 A B	7.0	9.0	2679	-	44	31.34	10.60	11.0	36.56

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Single Max Load (lbs)	Dual Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)							
07612	245/70R17 110T	STD	BSW	500 A B	6.5	8.0	2337	-	44	30.24	10.20	11.0	32.58
07678	LT285/70R17 121/118S	E	BSW	-	7.5	9.0	3195	2910	80	32.76	11.50	14.0	49.06
07620	275/65R18 116T	STD	BSW	500 A B	7.5	9.5	2756	-	44	31.85	11.00	11.0	38.50
07694	LT275/65R18 123/120S	E	BSW	-	7.5	9.0	3415	3085	80	32.09	11.00	14.0	49.06
07624	255/70R18 113T	STD	BSW	500 A B	6.5	8.5	2535	-	44	32.09	10.20	10.5	35.24
07702	LT275/70R18 125/122S	E	BSW	-	7.0	8.5	3640	3305	80	33.19	11.00	14.0	49.06
07628	265/70R18 116T	STD	BSW	500 A B	7.0	9.0	2756	-	44	32.56	10.70	10.5	36.96
07690	LT265/65R18 122/119R	E	BSW	-	7.5	9.5	3305	3000	80	32.09	11.00	14.0	47.08
07698	LT265/70R18 124/121S	E	BSW	-	7.0	9.0	3525	3195	80	32.64	10.70	14.0	47.08
07706	LT275/55R20 120/117S	E	BSW	-	7.5	9.5	3085	2835	80	34.09	11.00	14.0	53.46
07718	LT275/65R20 126/123S	E	BSW	-	7.5	9.5	3750	3415	80	34.09	11.00	14.0	53.31
07714	LT275/60R20 123/120S	E	BSW	-	7.5	9.5	3415	3085	80	34.09	11.00	14.0	52.82
07710	LT265/60R20 121/118R	E	BSW	-	7.5	9.5	3195	2910	80	31.65	10.50	14.0	51.70
07632	275/60R20 115T	STD	BSW	500 A B	7.5	9.5	2679	-	44	32.87	10.90	11.0	39.73

CUV/SUV/LT

# ALL COUNTRY® CHT



- Continuous shoulder rib fights irregular wear, helps increase tread life and improves steering response.
- Optimized tread pattern reduces noise for a more comfortable ride.
- Five-rib design promotes balanced tread wear and increases stability on a variety of road surfaces.
- Commercial grade construction and compounding ensures long running performance and trouble free mileage.
- Four wide circumferential grooves promote rapid water evacuation to help prevent hydroplaning.
- M+S Rated.



Item #	Tire Size & Service Description	Load Range	Sidewall	Approved Rim Width (in)		Single Max Load (lbs)	Dual Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
				Min Rim Width (in)	Max Rim Width (in)							
R-Speed Rated												
93701.1	LT215/85R16 115/112R	E	BSW	5.5	7.0	2680	2470	80	30.39	8.50	15.8	44.48
93704	LT235/85R16 120/116R	E	BSW	6.0	7.5	3042	2778	80	31.73	9.25	15.8	47.98
93702	LT225/75R16 115/112R	E	BSW	6.0	7.0	2680	2470	80	29.29	8.78	15.8	43.36
93706	LT245/75R16 120/116R	E	BSW	6.5	8.0	3042	2778	80	30.47	9.76	15.8	47.98
93709	LT265/75R16 123/120R	E	BSW	7.0	8.0	3415	3085	80	31.65	10.51	15.8	52.16
93703	LT235/80R17 120/117R	E	BSW	6.0	7.5	3085	2835	80	31.81	9.25	15.8	48.49
93707	LT245/75R17 121/118R	E	BSW	6.5	7.5	3195	2910	80	31.50	9.76	15.8	50.07
93705	LT245/70R17 119/116R	E	BSW	6.5	8.0	3000	2755	80	30.55	9.76	15.8	48.22
93708	LT265/70R17 121/118R	E	BSW	7.0	8.5	3195	2910	80	31.65	10.71	15.8	52.84
93711.1	LT275/70R18 125/122R	E	BSW	7.0	8.5	3640	3305	80	33.19	10.98	15.8	56.58
93710	LT275/65R18 123/120R	E	BSW	7.5	9.5	3415	3085	80	33.27	10.98	15.8	56.21

# ALL COUNTRY® HT



- Five-Rib Design combined with a unique tread element configuration, improves tread-life and reduces irregular wear.
- Optimized Pitch Sequence based on tread block geometry and groove dimension, delivers a quieter ride.
- Enhance Siping, Strategically placed fulldepth siping enhances wet surface traction and light snow performance.
- Four Wide Circumferential Grooves and robust construction, allow for fast water evacuation and highway stability.



Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Single Max Load (lbs)	Dual Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)							
T,R,S,H,V-Speed Rated													
03092	235/70R15 103T	STD	BW	500-A-B	6.0	8.0	1,929	-	44	27.99	9.40	10.5	25.56
03047	LT225/75R16 115/112R	E	BW	-	6.0	7.0	2,680	2,470	80	29.25	8.60	13.5	33.92
03049	LT245/75R16 120/116S	E	BW	-	6.5	8.0	3,042	2,778	80	30.31	9.60	13.5	38.06
03051	LT265/75R16 123/120S	E	BW	-	7.0	8.0	3,415	3,085	80	31.50	10.60	13.5	42.24
03059	235/70R16 106T	STD	BW	500-A-B	6.0	8.0	2,094	-	44	28.74	9.40	10.5	26.97
03061	245/70R16 107T	STD	BW	500-A-B	6.5	8.0	2,149	-	44	29.33	9.80	10.5	30.49
03063	255/70R16 111T	STD	BW	500-A-B	6.5	8.0	2,403	-	44	29.80	10.30	10.5	32.54
03065	265/70R16 112T	STD	BW	500-A-B	7.0	9.0	2,469	-	44	30.24	10.80	10.5	33.73
03067	225/75R16 104T	STD	BW	500-A-B	6.0	7.0	1,984	-	44	28.98	8.70	10.5	27.06
03069	245/75R16 111T	STD	BW	500-A-B	6.5	8.0	2,403	-	44	30.20	9.80	10.5	32.19
03071	265/75R16 116T	STD	BW	500-A-B	7.0	9.0	2,756	-	44	31.34	10.60	10.5	36.92
03088	215/70R16 100T	STD	BW	500-A-B	5.5	7.0	1,764	-	44	27.91	8.70	10.5	25.30
03090	225/70R16 103T	STD	BW	500-A-B	6.0	7.0	1,929	-	44	28.66	9.10	10.5	27.632
03053	LT245/75R17 121/118S	E	BW	-	6.5	7.5	3,195	2,910	80	31.54	10.00	13.5	42.702
03073	245/65R17 107T	STD	BW	500-A-B	7.0	8.5	2,149	-	44	29.49	9.60	10.5	30.14
03074	265/65R17 112T	STD	BW	500-A-B	7.5	9.5	2,469	-	44	30.39	10.60	10.5	34.45
03078	245/70R17 110T	STD	BW	500-A-B	6.5	8.0	2,337	-	44	30.24	10.20	10.5	30.54
03080	265/70R17 115T	STD	BW	500-A-B	7.0	9.0	2,679	-	44	31.34	10.60	10.5	35.57
03094	235/65R17 104H	STD	BW	500-A-B	6.5	8.5	1,984	-	44	29.25	9.60	10.5	28.86
03096	225/65R17 102T	STD	BW	500-A-B	6.0	8.0	1,874	-	44	28.54	9.20	10.5	26.82
03102	255/65R17 110T	STD	BW	500-A-B	7.0	9.0	2,337	-	44	30.16	10.10	10.5	32.12
03104	255/70R17 112T	STD	BW	500-A-B	6.5	8.5	2,469	-	44	31.10	10.20	10.5	33.51
03055	245/60R18 105H	STD	BW	500-A-B	7.0	8.5	2,039	-	44	29.69	9.60	10.5	29.92
03057	255/65R18 111T	STD	BW	500-A-B	7.0	9.0	2,403	-	44	31.10	10.10	10.5	34.10
03058	265/65R18 114T	STD	BW	500-A-B	7.5	9.5	2,601	-	44	31.50	10.70	10.5	36.08
03082	275/65R18 116T	STD	BW	500-A-B	7.5	9.5	2,756	-	44	31.85	11.00	10.5	37.40
03106	235/55R18 100H	STD	BW	500-A-B	6.5	8.5	1,764	-	44	28.27	9.80	10.5	28.12
03132	265/60R18 110H	STD	BW	500-A-B	7.5	9.5	2,337	-	44	30.55	10.50	10.5	35.88
03134	235/65R18 106H	STD	BW	500-A-B	6.5	8.5	2,094	-	44	30.08	9.40	10.5	31.46
03138	255/55R18 109V	XL	BW	500-A-B	7.0	9.0	2,271	-	50	29.06	10.40	10.5	35.42
03140	235/60R18 107H	XL	BW	500-A-B	6.5	8.5	2,149	-	50	29.09	9.50	10.5	55.00
03084	245/55R19 103T	STD	BW	500-A-B	7.0	8.5	1,929	-	44	29.69	9.80	10.5	30.71
03098	255/60R19 109H	STD	BW	500-A-B	7.0	9.0	2,271	-	44	31.22	10.10	10.5	33.77
03099	225/55R19 99V	STD	BW	500-A-B	6.0	8.0	1,709	-	44	28.78	9.10	10.5	28.91
03086	265/50R20 107T	STD	BW	500-A-B	7.5	9.5	2,149	-	44	30.47	10.90	10.5	33.77
03136	275/55R20 117H	XL	BW	500-A-B	7.5	9.5	2,833	-	50	31.73	10.90	10.5	40.19
03146	255/50R20 109V	XL	BW	500-A-B	7.0	9.0	2,271	-	50	30.08	10.40	10.5	34.78



# ALL COUNTRY® M/T



- Groove design enhances durability by protecting against stone drilling and puncture.
- Shoulder blocks easily shovel away mud, silt and sand and enhance traction on off-road surfaces.
- Staggered buttress design increases off-road capability and guards against high sidewall cuts and abrasions.
- Void ratio effectively promotes self-cleaning capability in muddy conditions.
- Three-ply sidewall protects against cutting and tearing in off-road situations.
- Studdable tread for extra "bite" in severe weather applications.



Approved Rim Width (in)

Item #	Tire Size & Service Description	Load Range	Sidewall	Min Rim Width (in)	Max Rim Width (in)	Single Max Load (lbs)	Dual Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)	Stud Size
97766	40x15.50R26 126Q	E	BSW	14.0	21.0	3750	-	65	39.80	15.60	21.0	106.20	15
92614	LT265/75R16 123/120Q	E	OWL	7.0	8.0	3415	3086	80	31.89	10.51	18.0	58.68	15
92615	LT285/75R16 126/123Q	E	OWL	7.5	9.0	3750	3417	80	33.07	11.26	18.0	62.66	15
92616	LT315/75R16 127/124Q	E	OWL	8.0	11.0	3860	3527	65	34.80	12.32	20.5	69.69	15
92619	LT235/80R17 120/117Q	E	BSW	6.0	7.5	3085	2833	80	32.05	9.25	18.0	49.53	15
92620	LT245/75R17 121/118Q	E	OWL	6.5	7.5	3195	2910	80	31.73	9.76	18.0	50.03	15
92621	LT265/70R17 121/118Q	E	OWL	7.0	8.5	3195	2910	80	31.89	10.71	19.5	59.26	15
92622	LT285/70R17 121/118Q	E	OWL	7.5	9.0	3195	2910	80	32.99	11.50	19.5	63.69	15
92623	LT315/70R17 121/118Q	E	BSW	8.0	11.0	3195	2910	65	34.65	12.72	19.5	71.08	15
98369	LT315/70R17 121/118Q	F	BSW	8.0	11.0	3195	2910	80	34.65	12.72	20.0	75.28	15
92625	LT275/65R18 123/120Q	E	BSW	7.5	9.5	3415	3086	80	32.32	10.98	19.5	59.87	15

Approved Rim Width (in)

Item #	Tire Size & Service Description	Load Range	Sidewall	Min Rim Width (in)	Max Rim Width (in)	Single Max Load (lbs)	Dual Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)	Stud Size
Q-Speed Rated													
92613	33X12.50R15 108Q	C	OWL	8.5	11.0	2205	-	35	32.76	12.52	19.5	63.28	15
92612	31X10.50R15 109Q	C	OWL	7.0	9.0	2270	-	50	30.75	10.55	18.0	47.44	15
92617	35X12.50R17 121Q	E	OWL	8.5	11.0	3195	-	65	34.76	12.52	20.5	78.93	15
98365	35X12.50R17 121Q	F	OWL	8.5	11.0	3195	-	80	34.76	12.52	21.0	75.88	15
92618	37X12.50R17 124Q	D	BSW	8.5	11.0	3525	-	50	36.77	12.52	20.5	81.44	15
98374	37X12.50R17 121Q	F	BSW	8.5	11.0	3195	-	80	36.77	12.52	21.0	78.59	15
92624	35X12.50R18 123Q	E	BSW	8.5	11.0	3415	-	65	34.76	12.52	20.5	78.72	15
98366	35X12.50R18 128Q	F	BSW	8.5	11.0	3970	-	80	34.76	12.52	21.0	75.69	15
95268	37X13.50R20 127Q	E	BSW	8.5	11.0	3860	-	65	36.77	13.58	20.7	86.75	15
98372	37X13.50R20 128Q	F	BSW	8.5	11.0	3970	-	80	36.77	13.58	21.0	88.88	15
92626	33X12.50R20 114Q	E	BSW	8.5	11.0	2600	-	65	32.76	12.52	20.5	75.12	15
98367	33X12.50R20 119Q	F	BSW	8.5	11.0	3000	-	80	32.76	12.52	21.0	73.73	15
92627	35X12.50R20 121Q	E	BSW	8.5	11.0	3195	-	65	34.76	12.52	20.5	79.54	15
98368	35X12.50R20 125Q	F	BSW	8.5	11.0	3640	-	80	34.76	12.52	21.0	81.60	15
95267	37X12.50R20 126Q	E	BSW	8.5	11.0	3750	-	65	36.77	12.52	20.7	82.06	15
98371	37X12.50R20 128Q	F	BSW	8.5	11.0	3970	-	80	36.77	12.52	21.0	82.94	15
95269	37X13.50R22 123Q	E	BSW	8.5	11.0	3415	-	65	36.77	13.58	20.7	87.85	15
98373	37X13.50R22 128Q	F	BSW	8.5	11.0	3970	-	80	36.77	13.58	21.0	88.30	15
95266	35X12.50R22 117Q	E	BSW	8.5	11.0	2835	-	65	34.76	12.52	20.7	76.41	15
97765	40x15.50R24 128Q	E	BSW	14.0	21.0	3970	-	65	39.80	15.60	21.0	104.80	15
98370	35X12.50R22 121Q	F	BSW	8.5	11.0	3195	-	80	34.76	12.52	21.0	77.14	15

# POLAR TRAX GEN2



- Directional tread design with V-Shaped lateral grooves enhance snow traction reinforced by rigid tread blocks.
- Silica compound maintains snow and ice performance, even in severe winter driving conditions.
- Zigzag center rib maximizes performance on ice and snow by beveled edge and tie-bars that improves straight line driving stability.
- New stud technology improves traction performance on snow and ice and minimizes road noise through optimum placement of stud pin holes.
- Heavy density, multi-wave sipes working in tandem with tread block shapes and arrangement, helps maximizing grip on ice and snow.
- Available in 47 sizes in 14-18 inch.

Item #	Tire Size & Service Description	Load Range	Sidewall	Approved Rim Width (in)		Single Max Load (lbs)	Dual Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)	Stud Size
				Min Rim Width (in)	Max Rim Width (in)								
T,R,Q-Speed Rated													15
98282	175/70R14 84T	STD	BSW	4.5	6.0	1102	-	44	23.70	7.00	12.0	16.26	12
98285	185/70R14 92T	XL	BSW	4.5	6.0	1389	-	50	24.30	7.40	12.0	18.66	12
98281	175/65R14 86T	XL	BSW	5.0	6.0	1168	-	50	23.00	7.00	12.0	16.45	12
98284	185/65R14 90T	XL	BSW	5.0	6.5	1323	-	50	23.50	7.40	12.0	18.24	12
98283	185/60R14 82T	STD	BSW	5.0	6.5	1047	-	44	22.80	7.40	12.0	16.17	12
98293	235/75R15 105T	STD	BSW	6.0	8.0	2039	-	44	28.90	9.30	12.5	31.74	12
98292	215/70R15 98T	STD	BSW	5.5	7.0	1653	-	44	26.90	8.70	12.0	23.96	12
98288	185/65R15 92T	XL	BSW	5.0	6.5	1389	-	50	24.40	7.40	12.0	19.64	12
98290.1	195/65R15 95T	XL	BSW	5.5	7.0	1521	-	50	25.00	7.90	12.0	21.36	12
98291	205/65R15 99T	XL	BSW	5.5	7.5	1709	-	50	25.50	8.20	12.0	22.98	12
98287	185/60R15 88T	XL	BSW	5.0	6.5	1235	-	50	23.70	7.40	12.0	17.85	12
98289	195/60R15 92T	XL	BSW	5.5	7.0	1389	-	50	24.20	7.90	12.0	19.34	12
98286	185/55R15 86T	XL	BSW	5.0	6.5	1168	-	50	23.00	7.60	12.0	17.63	12
98303	245/75R16 111T	STD	BSW	6.5	8.0	2403	-	44	30.50	9.80	12.5	33.4	12
98299	215/70R16 100T	STD	BSW	5.5	7.0	1764	-	44	27.90	8.70	12.5	25.97	12
98301	225/70R16 107T	XL	BSW	6.0	7.5	2149	-	50	28.40	9.00	12.5	28.62	12
98302	235/70R16 106T	STD	BSW	6.0	8.0	2094	-	44	29.00	9.40	12.5	30.56	12
98304	265/70R16 112T	STD	BSW	7.0	9.0	2469	-	44	30.60	10.70	12.5	35.21	12

Approved Rim Width (in)

Item #	Tire Size & Service Description	Load Range	Sidewall	Approved Rim Width (in)		Single Max Load (lbs)	Dual Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)	Stud Size
				Min Rim Width (in)	Max Rim Width (in)								
98298	215/65R16 102T	XL	BSW	6.0	7.5	1874	-	50	27.00	8.7	12.0	26	12
98323	235/65R16C 121/119R	E	BSW	6.5	7.5	3197	2998	83	28.00	9.4	12.5	37.41	15
98295	205/60R16 92T	STD	BSW	5.5	7.5	1389	-	44	25.70	8.2	12.0	20.22	12
98297	215/60R16 99T	XL	BSW	6.0	7.5	1709	-	50	26.10	8.7	12.0	24.2	12
98300	225/60R16 102T	XL	BSW	6.0	8.0	1874	-	50	26.60	9.0	12.0	25.6	12
98294	205/55R16 94T	XL	BSW	5.5	7.5	1477	-	50	24.90	8.4	12.0	20.83	12
98296	215/55R16 97T	XL	BSW	6.0	7.5	1609	-	50	25.30	8.9	12.0	24.03	12
98316	245/70R17 110T	STD	BSW	6.5	8.0	2337	-	44	30.60	9.8	12.5	34	12
98317	265/70R17 115T	STD	BSW	7.0	9.0	2679	-	44	31.70	10.7	12.5	39.55	12
98312	225/65R17 106T	XL	BSW	6.0	8.0	2094	-	50	28.50	9.0	12.5	29.06	12
98314	235/65R17 108T	XL	BSW	6.5	8.5	2205	-	50	29.10	9.4	12.5	31.17	12
98315	245/65R17 107T	STD	BSW	7.0	8.5	2149	-	44	29.50	9.8	12.5	32	12
98307	215/60R17 100T	XL	BSW	6.0	7.5	1764	-	50	27.20	8.7	12.0	25.6	12
98311	225/60R17 99T	STD	BSW	6.0	8.0	1709	-	44	27.60	9.0	12.5	27.12	12
98306	215/55R17 98T	XL	BSW	6.0	7.5	1653	-	50	26.30	8.9	12.0	25.3	12
98310	225/55R17 101T	XL	BSW	6.0	8.0	1819	-	50	26.80	9.2	12.0	26.13	12
98313	235/55R17 103T	XL	BSW	6.5	8.5	1929	-	50	27.20	9.6	12.0	28.05	12
98305	215/50R17 95T	XL	BSW	6.0	7.5	1521	-	50	25.50	8.9	12.0	22.28	12
98309	225/50R17 98T	XL	BSW	6.0	8.0	1653	-	50	25.90	9.2	12.0	25.01	12
98308	225/45R17 91T	STD	BSW	7.0	8.5	1356	-	44	25.00	8.9	12.0	22.64	12
98319	225/60R18 100T	STD	BSW	6.0	8.0	1764	-	44	28.60	9.0	12.5	28.41	12
98321	235/60R18 107T	XL	BSW	6.5	8.5	2149	-	50	29.10	9.4	12.5	29.99	12
98322	245/60R18 105T	STD	BSW	7.0	8.5	2039	-	44	29.60	9.8	12.5	32.3	12
98318	225/55R18 98T	STD	BSW	6.0	8.0	1653	-	44	27.80	9.2	12.5	28.11	12
98320	235/55R18 100T	STD	BSW	6.5	8.5	1764	-	44	28.10	9.6	12.5	29.42	12
98324	LT225/75R16 115/112Q	E	BSW	6.0	7.0	2680	2470	80	29.30	8.8	16.0	38.13	15
98325	LT245/75R16 120/116Q	E	BSW	6.5	8.0	3042	2778	80	30.50	9.8	16.0	42.77	15
98326	LT265/75R16 123/120Q	E	BSW	7.0	8.0	3415	3085	80	31.70	10.5	16.0	50.92	15
98327	LT265/70R17 121/118Q	E	BSW	7.0	8.5	3195	2910	80	31.70	10.7	16.0	50.01	15

WINTER

# iMOVE® GEN2AS



- Asymmetric tread design provides enhanced traction and responsive handling in wet and dry conditions.
- New generation, wear-resistant compound enhances durability for extended tread life.
- Enhanced tread block geometry and siping placement improves grip and minimizes road noise.
- Improved pressure distribution provides even wear and extends tread life.
- Circumferential and longitudinal grooves maximize water evacuation to minimize hydroplane risk.
- M+S rated.

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)						
T,H,V,W-Speed Rated												
92987	185/70R14 88T	STD	BSW	460 A B	4.5	6.0	1235	44	24.25	7.44	10.1	17.44
92988	195/70R14 91T	STD	BSW	460 A B	5.0	6.5	1356	44	24.80	7.91	10.1	18.91
92986	185/65R14 86H	STD	BSW	420 A A	5.0	6.5	1168	44	23.46	7.44	10.1	16.78
92985	185/60R14 82H	STD	BSW	420 A A	5.0	6.5	1047	44	22.76	7.44	10.1	16.16
92996	205/70R15 96T	STD	BSW	460 A B	5.0	7.0	1565	44	26.34	8.23	10.1	22.99
93060	215/70R15 98T	STD	BSW	460 A B	5.5	7.0	1653	44	26.89	8.70	10.3	23.97
92993	185/65R15 88H	STD	BSW	420 A A	5.0	6.5	1235	44	24.45	7.44	10.1	17.31
92994	195/65R15 91H	STD	BSW	420 A A	5.5	7.0	1356	44	25.00	7.91	10.1	20.02
92995	205/65R15 94H	STD	BSW	420 A A	5.5	7.5	1477	44	25.47	8.23	10.1	20.90
92991	195/60R15 88H	STD	BSW	420 A A	5.5	7.0	1235	44	24.21	7.91	10.1	18.70
92992	205/60R15 91H	STD	BSW	420 A A	5.5	7.5	1356	44	24.68	8.23	10.1	19.40
93682	185/55R15 82V	STD	BSW	420 A A	5.0	6.5	1047	44	23.03	7.28	10.1	16.15
92990	195/55R15 85V	STD	BSW	420 A A	5.5	7.0	1135	44	23.43	7.91	10.1	17.88
92989	195/50R15 82V	STD	BSW	420 A A	5.5	7.0	1047	44	22.72	7.91	10.1	17.01
93006	215/65R16 98H	STD	BSW	420 A A	6.0	7.5	1653	44	27.01	8.70	10.3	23.87
93003	205/60R16 92V	STD	BSW	420 A A	5.5	7.5	1389	44	25.67	8.23	10.1	20.35
93004	215/60R16 95V	STD	BSW	420 A A	6.0	7.5	1521	44	26.14	8.70	10.3	22.64
93005	225/60R16 98H	STD	BSW	420 A A	6.0	8.0	1653	44	26.61	8.98	10.3	23.63
93000	205/55R16 91V	STD	BSW	420 A A	5.5	7.5	1356	44	24.88	8.43	10.1	20.24
93001	215/55ZR16 97W	XL	BSW	380 A A	6.0	7.5	1609	50	25.28	8.90	10.3	21.89
93002	225/55R16 99H	XL	BSW	420 A A	6.0	8.0	1709	50	25.75	9.17	10.3	22.82
92998	205/50ZR16 91W	XL	BSW	380 A A	5.5	7.5	1356	50	24.09	8.43	10.1	19.90
92999	225/50R16 96V	XL	BSW	420 A A	6.0	8.0	1565	50	24.88	9.17	10.3	22.49
92997	205/45ZR16 87W	XL	BSW	380 A A	6.5	7.5	1201	50	23.23	8.11	10.1	17.91

Approved Rim Width (in)

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)						
93015	215/55R17 94V	STD	BSW	420 A A	6.0	7.5	1477	44	26.30	8.90	10.3	22.71
93016	225/55R17 97H	STD	BSW	420 A A	6.0	8.0	1609	44	26.77	9.17	10.3	24.46
93017	235/55R17 103V	XL	BSW	420 A A	6.5	8.5	1929	50	27.17	9.65	10.3	25.99
93011	205/50ZR17 93W	XL	BSW	380 A A	5.5	7.5	1433	50	25.12	8.43	10.1	21.08
93012	215/50R17 95V	XL	BSW	420 A A	6.0	7.5	1521	50	25.51	8.90	10.3	22.90
93013	225/50R17 94V	STD	BSW	420 A A	6.0	8.0	1477	44	25.91	9.17	10.3	24.14
93014	235/50ZR17 96W	STD	BSW	380 A A	6.0	8.5	1565	44	26.30	9.65	10.3	25.08
93679	205/45ZR17 88W	XL	BSW	380 A A	6.5	8.0	1235	50	24.25	8.07	10.1	18.30
93008	215/45ZR17 91W	XL	BSW	380 A A	7.0	8.0	1356	50	24.65	8.39	10.3	20.56
93009	225/45ZR17 94W	XL	BSW	380 A A	7.0	8.5	1477	50	24.96	8.86	10.3	21.85
93010	235/45ZR17 97W	XL	BSW	380 A A	7.5	9.0	1609	50	25.35	9.29	10.3	23.10
93680	245/45ZR17 99W	XL	BSW	380 A A	7.5	9.0	1653	50	25.67	9.65	10.3	24.19
93007	205/40ZR17 84W	XL	BSW	380 A A	7.0	8.0	1102	50	23.46	8.35	10.1	19.17
93676	245/40ZR17 95W	XL	BSW	380 A A	8.0	9.5	1521	50	24.72	9.65	10.3	22.90
97859	225/60R18 100V	STD	BSW	420 A A	6.5	6.5	1764	44	28.62	8.98	10.0	27.34
93683	235/55R18 100V	STD	BSW	420 A A	6.5	8.5	1764	44	28.15	9.25	10.3	26.92
93025	225/50ZR1895W	STD	BSW	380 A A	6.0	8.0	1521	44	26.89	9.17	10.3	24.44
93026	235/50ZR18 97W	STD	BSW	380 A A	6.5	8.5	1609	44	27.28	9.65	10.3	26.38
96584	245/50ZR18 100W	STD	BSW	380 A A	7.0	8.5	1764	44	27.68	9.96	10.0	28.22
93022	225/45ZR18 91W	STD	BSW	380 A A	7.0	8.5	1356	44	25.94	8.86	10.3	22.80
93023	235/45ZR18 94W	STD	BSW	380 A A	7.5	9.0	1477	44	26.34	9.29	10.3	24.29
93024	245/45ZR18 100W	XL	BSW	380 A A	7.5	9.0	1764	50	26.65	9.57	10.3	25.52
93019	225/40ZR18 92W	XL	BSW	380 A A	7.5	9.0	1389	50	25.08	9.06	10.3	22.06
93020	235/40ZR18 95W	XL	BSW	380 A A	8.0	9.5	1521	50	25.39	9.49	10.3	23.14
93021	245/40ZR18 97W	XL	BSW	380 A A	8.0	9.5	1609	50	25.71	9.76	10.3	24.43
93018	255/35ZR18 94W	XL	BSW	380 A A	8.5	10.0	1477	50	25.00	10.24	10.3	23.96
93684	235/55R19 105V	XL	BSW	420 A A	6.5	8.5	2039	50	29.17	9.25	10.3	29.15
96585	235/50R19 103V	XL	BSW	380 A A	6.5	8.5	1929	50	28.70	9.65	10.0	27.56
97860.1	245/45ZR19 102W	XL	BSW	380 A A	8.0	8.0	1874	50	27.70	9.57	10.0	29.10
93677	245/40ZR19 98W	XL	BSW	380 A A	8.0	9.5	1653	50	26.73	9.65	10.3	25.13
93029	225/35ZR19 88W	XL	BSW	380 A A	7.5	9.0	1235	50	25.24	9.06	10.3	21.33
93030	235/35ZR19 91W	XL	BSW	380 A A	8.0	9.5	1356	50	25.47	9.49	10.3	22.33
93031	255/35ZR19 96W	XL	BSW	380 A A	8.0	9.5	1565	50	26.02	10.24	10.3	24.97
93027	265/30ZR19 93W	XL	BSW	380 A A	9.0	10.5	1433	50	25.31	10.67	10.3	25.29
93028	275/30ZR19 96W	XL	BSW	380 A A	9.0	10.0	1565	50	25.55	10.94	10.3	26.18
97861	245/50R20 102V	STD	BSW	420 A A	7.5	7.5	1874	44	29.71	9.96	11.0	33.29
93681	245/45ZR20 103W	XL	BSW	380 A A	7.5	9.0	1929	50	28.66	9.65	10.3	27.69
96586	255/45ZR20 105W	XL	BSW	380 A A	8.0	9.5	2039	50	29.06	10.04	11.0	29.54
93678	245/40ZR20 99W	XL	BSW	380 A A	8.0	9.5	1709	50	27.72	9.65	10.3	26.28
93032	225/35ZR20 90W	XL	BSW	380 A A	7.5	9.0	1323	50	26.22	9.06	10.3	22.37
93033	245/35ZR20 95W	XL	BSW	380 A A	8.0	9.5	1521	50	26.77	9.76	10.3	24.78
93675	255/35ZR20 97W	XL	BSW	380 A A	8.5	10.0	1609	50	27.01	10.04	10.3	25.75
93674	245/30ZR22 92W	XL	BSW	380 A A	8.0	9.0	1389	50	27.83	9.65	10.3	25.31

SPECIAL ORDER

# GR 906



- Modern symmetric tread design promotes even wear and assured handling.
- Tread elements minimize road noise, increase stability and aid in traction.
- High-density siping enhances wet and snow traction.
- All-season touring compound improves wet surface traction and promotes lower rolling resistance.
- M+S Rated.

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)						
T,H,V-Speed Rated												
92582	155/80R13 79T	STD	BSW	440 A A	4.0	5.0	963	44	22.80	6.20	9.5	13.89
92580	175/70R13 82T	STD	BSW	440 A A	4.5	6.0	1047	44	22.70	7.00	9.5	14.33
92581	185/70R13 86T	STD	BSW	440 A A	4.5	6.0	1168	44	23.20	7.40	9.5	15.21
92586	175/70R14 84T	STD	BSW	440 A A	4.5	6.0	1102	44	23.70	7.00	9.5	15.21
92587	185/70R14 88T	STD	BSW	440 A A	4.5	6.0	1235	44	24.30	7.40	9.5	16.98
92588	195/70R14 91T	STD	BSW	440 A A	5.0	6.5	1356	44	24.80	7.90	9.8	18.96
92589	205/70R14 95T	STD	BSW	440 A A	5.0	7.0	1521	44	25.40	8.20	9.8	20.50
92584.1	175/65R14 82H	STD	BSW	440 A A	5.0	6.0	1047	44	23.00	7.00	9.5	14.77
92585	185/65R14 86H	STD	BSW	440 A A	5.0	6.5	1168	44	23.50	7.40	9.5	15.87
92583	195/60R14 86H	STD	BSW	440 A A	5.5	7.0	1168	44	23.20	7.90	9.8	16.75
92598	205/70R15 96H	STD	BSW	440 A A	5.0	7.0	1565	44	26.30	8.20	9.8	22.05
92599	215/70R15 98H	STD	BSW	440 A A	5.5	7.0	1653	44	26.90	8.70	9.8	23.37
92600	225/70R15 100T	STD	BSW	440 A A	6.0	7.5	1764	44	27.40	9.00	9.8	24.69
92594	185/65R15 88H	STD	BSW	440 A A	5.0	6.5	1235	44	24.40	7.40	9.5	17.20
92595	195/65R15 91H	STD	BSW	440 A A	5.5	7.0	1356	44	25.00	7.90	9.8	19.18
92596	205/65R15 94H	STD	BSW	440 A A	5.5	7.5	1477	44	25.50	8.20	9.8	20.50
92597	215/65R15 96H	STD	BSW	440 A A	6.0	7.5	1565	44	26.00	8.70	9.8	22.49
92590	185/60R15 84H	STD	BSW	440 A A	5.0	6.5	1102	44	23.70	7.40	9.5	16.53
92591	195/60R15 88H	STD	BSW	440 A A	5.5	7.0	1235	44	24.20	7.90	9.8	19.18
92592	205/60R15 91H	STD	BSW	440 A A	5.5	7.5	1356	44	24.70	8.20	9.8	19.62

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)						
92593.1	215/60R15 94H	STD	BSW	440 A A	6.0	7.5	1477	44	25.20	8.70	9.8	21.61
92607	205/65R16 95H	STD	BSW	440 A A	5.5	7.5	1521	44	26.50	8.20	9.8	23.15
92608	215/65R16 98H	STD	BSW	440 A A	6.0	7.5	1653	44	27.00	8.70	9.8	24.25
92609	225/65R16 100H	STD	BSW	440 A A	6.0	8.0	1764	44	27.50	9.00	9.8	25.57
92610	235/65R16 103H	STD	BSW	440 A A	6.5	8.5	1929	44	28.00	9.40	9.8	27.56
92603	205/60R16 92H	STD	BSW	440 A A	5.5	7.5	1389	44	25.70	8.20	9.8	20.94
92604	215/60R16 95H	STD	BSW	440 A A	6.0	7.5	1521	44	26.10	8.70	9.8	22.93
92605	225/60R16 98H	STD	BSW	440 A A	6.0	8.0	1653	44	26.60	9.00	9.8	24.25
92606	235/60R16 100H	STD	BSW	440 A A	6.5	8.5	1764	44	27.10	9.40	9.8	25.79
92602	205/55R16 91V	STD	BSW	440 A A	5.5	7.5	1356	44	24.90	8.40	9.8	20.50
92601	205/50R16 87V	STD	BSW	440 A A	5.5	7.5	1201	44	24.10	8.40	9.8	19.62
97876	215/65R17 99T	STD	BSW	440 A A	6.0	7.5	1709	44	28.00	8.70	9.8	24.94
97877	225/65R17 102H	STD	BSW	440 A A	6.0	8.0	1874	44	28.50	8.90	9.8	26.41
96610	215/60R17 96H	STD	BSW	440 A A	6.5	6.5	1565	44	27.20	8.70	9.8	24.40
96612	225/60R17 99H	STD	BSW	440 A A	6.5	6.5	1709	44	27.60	9.00	9.8	25.40
97878	235/60R17 102H	STD	BSW	440 A A	6.5	8.5	1874	44	28.11	9.44	9.8	26.82
96609.1	215/55R17 94H	STD	BSW	440 A A	7.0	7.0	1477	44	26.30	8.90	9.8	22.70
96611	225/55R17 97H	STD	BSW	440 A A	7.0	7.0	1609	44	26.80	9.20	9.8	24.60
96613	235/55R17 99H	STD	BSW	440 A A	7.5	7.5	1709	44	27.20	9.60	9.8	27.30

# ALL COUNTRY® AT



- Large tread blocks and deep grooves ensure superb off-road traction.
- Wide angled lateral grooves and void ratio enhance mud, water, and snow evacuation for all-surface traction performance.
- Buttress design enhances traction in muddy conditions and guards against puncture.
- Tread compound adds longevity and promotes enhanced wet traction.
- M+S Rated.

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Single Max Load (lbs)	Dual Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)							
91196.1	235/75R15 109T	XL	BSW	460 A B	6.0	8.0	2271	-	50	28.86	9.25	13.4	32.61
91198	245/75R16 111T	STD	BSW	460 A B	6.5	8.0	2403	-	44	30.47	9.76	13.4	35.22
91203	265/75R16 116T	STD	BSW	460 A B	7.0	9.0	2756	-	44	31.64	10.51	13.4	39.27
91195	235/70R16 106T	STD	BSW	460 A B	6.0	8.0	2094	-	44	28.98	9.45	13.4	33.07
91197	245/70R16 111T	XL	BSW	460 A B	6.5	8.0	2403	-	49	29.52	9.76	13.4	34.44
91199	255/70R16 111T	STD	BSW	460 A B	6.5	8.5	2403	-	44	30.08	10.24	13.4	36.09
91201	265/70R16 112T	STD	BSW	460 A B	7.0	9.0	2469	-	44	30.63	10.71	13.4	37.88
91202	265/70R17 115T	STD	BSW	460 A B	7.0	9.0	2679	-	44	31.65	10.71	13.4	40.24
91200	265/65R17 112T	STD	BSW	460 A B	7.5	9.5	2469	-	44	30.16	10.71	13.4	38.23
97829	255/70R18 113T	STD	BSW	460 A B	7.5	7.5	2536	-	44	32.09	10.24	13.0	39.10
96595	265/70R18 116T	STD	BSW	460 A B	7.0	9.0	2756	-	44	32.63	10.71	13.6	45.00
91204	275/65R18 116T	STD	BSW	460 A B	7.5	9.5	2756	-	44	32.08	10.98	13.4	41.60
96596	275/60R20 115H	STD	BSW	460 A B	7.5	9.5	2679	-	44	32.99	10.98	13.6	46.36
91205.2	31X10.50R15 109Q	C	BSW	-	7.0	9.0	2271	-	50	30.51	10.55	15.6	41.36
91207	LT235/75R15 104/101Q	C	BSW	-	6.0	7.0	1985	1820	50	28.86	9.25	15.6	35.96
93218	LT215/85R16 115/112Q	E	BSW	-	5.5	7.0	2680	2470	80	30.38	8.50	13.9	37.43
93220	LT235/85R16 120/116Q	E	BSW	-	6.0	7.5	3042	2778	80	31.70	9.25	15.4	41.91
91206	LT225/75R16 115/112Q	E	BSW	-	6.0	7.0	2680	2470	80	29.30	8.78	15.6	38.49
91208.1	LT245/75R16 120/116Q	E	BSW	-	6.5	8.0	3042	2778	80	30.48	9.76	15.6	43.08
91210	LT265/75R16 123/120Q	E	BSW	-	7.0	8.0	3415	3085	80	31.65	10.51	15.6	47.33
91211.1	LT285/75R16 126/123Q	E	BSW	-	7.5	9.0	3750	3415	80	32.84	11.26	15.6	51.59
93219	LT235/80R17 120/117Q	E	BSW	-	6.0	7.5	3085	2835	80	31.80	9.25	15.4	42.13

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Single Max Load (lbs)	Dual Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)							
93222.1	LT245/75R17 121/118Q	E	BSW	-	6.5	7.5	3195	2910	80	31.49	9.76	15.4	43.74
93221	LT245/70R17 119/116Q	E	BSW	-	6.5	8.0	3000	2755	80	30.55	9.76	15.4	42.77
91209	LT265/70R17 121/118Q	E	BSW	-	7.0	8.5	3195	2910	80	31.65	10.71	15.6	47.54
93225.1	LT285/70R17 121/118Q	D	BSW	-	7.5	9.0	3195	2910	80	32.75	11.49	16.0	54.30
96598	LT265/70R18 124/121Q	E	BSW	-	7.0	9.0	3525	3195	80	32.63	10.71	15.7	53.17
93224.1	LT275/70R18 125/122Q	E	BSW	-	7.0	8.5	3640	3305	80	33.19	10.98	16.0	52.69
96597	LT265/65R18 122/119Q	E	BSW	-	7.5	9.5	3305	3000	80	31.53	10.71	15.7	46.36
93223.1	LT275/65R18 123/120Q	E	BSW	-	7.5	9.5	3415	3085	80	32.08	10.98	16.0	50.18
96599	LT275/65R20 126/123Q	E	BSW	-	7.5	9.5	3750	3415	80	34.09	10.98	15.7	54.32
97831	LT275/60R20 123/120Q	E	BSW	-	8.0	8.0	3415	3085	80	32.99	10.98	15.0	51.86
97830	LT275/55R20 120/117Q	E	BSW	-	8.5	8.5	3085	2835	80	31.89	11.18	15.0	48.82

# RB-SUV & RB-LT



- Highway touring design delivers extended mileage.
- Tread design and placement of tread elements reduce noise and enhance overall ride comfort.
- Wide circumferential grooves ensure excellent water evacuation while lateral grooves optimize braking performance.
- Shoulder design enhances cornering performance and stability at higher speeds.
- Solid center rib promotes straight-line stability.
- M+S Rated.

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Single Max Load (lbs)	Dual Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)							
<b>IRONMAN RB-SUV</b>													
S,T,H-Speed Rated													
91181	235/75R15 105S	STD	OWL	460 A B	6.0	8.0	2040	-	44	28.88	9.25	11.6	30.04
91179	235/70R15 103S	STD	OWL	460 A B	6.0	8.0	1929	-	44	28.01	9.45	11.6	31.44
91178	225/75R16 104S	STD	OWL	460 A B	6.0	7.5	1985	-	44	29.30	8.78	11.6	32.32
91185	245/75R16 111S	STD	OWL	460 A B	6.5	8.0	2404	-	44	30.50	9.76	11.6	36.02
91189	265/75R16 116S	STD	OWL	460 A B	7.0	9.0	2756	-	44	31.68	10.51	11.6	40.21
91177.1	215/70R16 100S	STD	BSW	460 A B	5.5	7.0	1764	-	44	27.87	8.70	11.6	27.30
93209.1	225/70R16 103T	STD	BSW	460 A B	6.0	7.5	1929	-	44	28.42	8.90	10.7	27.19
91180	235/70R16 106S	STD	OWL	460 A B	6.0	8.0	2095	-	44	29.00	9.40	11.6	33.11
91183	245/70R16 107S	STD	OWL	460 A B	6.5	8.0	2150	-	44	29.55	9.76	11.6	33.39
91186	255/70R16 11S	STD	OWL	460 A B	6.5	8.5	2404	-	44	30.10	10.20	11.6	36.70
91187	265/70R16 112S	STD	OWL	460 A B	7.0	9.0	2470	-	44	30.65	10.71	11.6	38.62
91191	235/70R17 107T	STD	BSW	460 A B	6.0	8.0	2150	-	44	30.00	9.45	11.6	31.47
91184	245/70R17 110S	STD	OWL	460 A B	6.5	8.0	2337	-	44	30.61	9.61	11.6	35.07
93213.1	255/70R17 112T	STD	OWL	460 A B	6.5	8.5	2470	-	44	31.10	10.20	10.7	34.30
91188.1	265/70R17 115S	STD	OWL	460 A B	7.0	9.0	2679	-	44	31.68	10.71	11.6	40.28
91190	225/65R17 102T	STD	OWL	460 A B	6.0	8.0	1874	-	44	28.50	8.98	11.6	27.99
93210.1	235/65R17 104H	STD	BSW	460 A B	6.5	8.5	1985	-	44	29.05	9.40	10.7	27.98
91182	245/65R17 107S	STD	OWL	460 A B	7.0	8.5	2150	-	44	29.55	9.49	11.6	38.48
93212.1	255/65R17 110T	STD	OWL	460 A B	7.0	9.0	2337	-	44	30.08	10.20	10.7	33.47
93215.1	265/65R17 112T	STD	OWL	460 A B	7.5	9.5	2470	-	44	30.56	10.70	10.7	34.98

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Approved Rim Width (in)		Single Max Load (lbs)	Dual Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)
					Min Rim Width (in)	Max Rim Width (in)							
93211	235/65R18 106H	STD	BSW	460 A B	6.5	8.5	2095	-	44	30.02	9.40	10.7	29.63
96593	255/65R18 111T	STD	BSW	460 A B	7.0	9.0	2403	-	44	30.98	10.24	10.3	36.60
93216.1	265/65R18 114T	STD	OWL	460 A B	7.5	9.5	2602	-	44	31.53	10.70	10.7	42.76
93217.1	275/65R18 116T	STD	OWL	460 A B	7.5	9.5	2756	-	44	32.08	10.90	10.7	37.95
96591.1	235/60R18 107H	XL	BSW	460 A B	6.6	8.6	2149	-	50	29.02	9.45	10.3	30.45
96592	245/60R18 105H	STD	BSW	460 A B	7.0	8.5	2039	-	44	29.49	9.76	10.3	30.91
93214.1	265/60R18 110H	STD	BSW	460 A B	7.5	9.5	2337	-	44	30.52	10.70	10.7	34.87
96590	235/55R18 100H	STD	BSW	460 A B	6.5	8.5	1764	-	44	28.03	9.65	9.8	29.32
97827	255/55R18 109V	XL	BSW	-	8.0	8.0	2040	-	44	29.02	10.43	9.4	31.70
97828	255/60R19 109H	STD	BSW	-	7.5	7.5	2271	-	44	31.06	10.24	9.7	33.67
96594	275/55R20 117T	STD	BSW	460 A B	7.5	9.5	2833	-	50	31.81	11.18	9.8	39.55
97826	255/50R20 109V	XL	BSW	-	8.0	8.0	2271	-	50	30.08	10.43	9.7	32.93

<b>IRONMAN RB-LT</b>													
Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Min Rim Width (in)	Max Rim Width (in)	Single Max Load (lbs)	Dual Max Load (lbs)	Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)
91192	LT245/75R16 120/116S	E	OWL	-	6.5	8.0	3042	2778	80	30.47	9.76	13.5	39.05
91194	LT265/75R16 123/120S	E	OWL	-	7.0	8.0	3415	3085	80	31.65	10.51	13.5	44.87
91193	LT265/70R17 121/118S	E	OWL	-	7.0	8.5	3195	2910	80	31.65	10.71	13.5	50.50

# LIMITED PROTECTION POLICY

## IRONMAN® TIRES LIMITED PROTECTION POLICY

**This Limited Protection Policy applies to Ironman brand tires purchased on or after January 1, 2018, or, in the absence of proof of purchase, tires with a manufacturing DOT code reading DOT 0118 or later.**

This policy is applicable in the United States and Canada only. Ironman Tires is a brand of the Hercules Tire & Rubber Co. THIS LIMITED PROTECTION POLICY IS NOT A GUARANTEE THAT YOUR TIRE WILL NOT FAIL OR BECOME UNSERVICEABLE IF NEGLECTED OR MISTREATED.

### IMPORTANT

The following contains important information that you must have in order to obtain an adjustment under the terms of the protection policy. We suggest you keep this in your vehicle at all times. In the unlikely event that you ever need to request an adjustment under the terms of the protection policy, present this to your Ironman Tires dealer and they will have all the information needed to promptly address your request.

### ELIGIBILITY

Eligible tires are covered by this Limited Protection Policy for a period of 60 months from the date of original tire manufacture date or purchase date. Without proof of purchase, date of manufacture will be used to determine age.

This Limited Protection Policy applies to the original owner of new Ironman brand SUV/P-Metric/Light Truck and Passenger tires that are new replacement market tires bearing the Ironman brand name and D.O.T. Tire Identification Number, operated in normal service, and used on the same vehicle on which they were originally installed according to the vehicle manufacturer's recommendations. Tire(s) on any vehicle registered and normally operated outside the United States and Canada are excluded from eligibility under this Limited Protection Policy.

When used in normal noncommercial service, SUV/P-Metric/Light Truck and Passenger tires which become unserviceable due to defects in workmanship and material will be replaced on a "no charge" basis during the first 2/32nds of an inch (1.6mm) of original usable tread. The cost of mounting, balancing and any other service charges including applicable taxes are excluded from reimbursement. Thereafter, the adjustment replacement price will be based upon tread wear prorated upon the basis of the original purchase price. Tires are considered 100% worn when the remaining tread depth is 2/32nds of an inch or less. Cosmetically blemished ("blem") tires are not adjustable. Out of balance, out of round or ride disturbance tire adjustments will only be made during the first 2/32nds of an inch of the original usable tread depth. Three (3) or more tires from the same vehicle will not be accepted. All Ironman brand tire adjustments will be subject to and made in conformity with the following conditions and exclusions of the Ironman Limited Protection Policy.

**IMPORTANT SAFETY NOTICE: IF THE TIRE OWNER ABUSES THE TIRES BY FAILING TO OBSERVE SAFETY WARNINGS AND TO MAINTAIN PROPER INFLATION PRESSURE, VEHICLE ALIGNMENT AND TIRE ROTATION, EXPECTED TIRE PERFORMANCE AND LIFE MAY NOT BE ACHIEVED, AND YOUR SAFETY CANNOT BE ENSURED.**

Hercules Tire & Rubber Co. cares about your safety and your tires. Please drive responsibly and maintain your vehicle properly. Visit our website for important tire safety tips provided by the Rubber Manufacturers' Association. We encourage every consumer to "Be Tire Smart, Play Your P.A.R.T." by understanding and practicing the additional tire safety tips available online at [www.rma.org](http://www.rma.org).

To be eligible, you need to present your original tire sales invoice showing date of purchase, along with this Limited Protection Policy, with the Information Section completed. You are responsible for payment of all applicable taxes, demounting, mounting and balancing charges set forth under this Coverage. You are also responsible for payment of local tire disposal fees and any parts or service regardless of mileage or months of service. This includes payment for tire rotation, alignment, towing, road service and valve stems and all applicable taxes.

Tires replaced on an adjustment basis become the property of the Company. You will be required to sign the Ironman Limited Protection Policy Claim Form.

Adjustment procedures are described in the Owner's General Obligation section. Complete and sign an Ironman Limited Protection Policy Claim Form which is available at any authorized dealer.

### WHAT IS NOT COVERED BY THIS LIMITED PROTECTION POLICY

THE FOLLOWING ARE NOT COVERED:

- Hercules Tire & Rubber Co. does not warrant any repaired or cosmetically blemished ("blem") tire.
- Road hazards (i.e. cuts, snags, punctures, sidewall curbs, potholes, impact, stone drills, etc.)
- Improper operation or maintenance: This includes, but is not limited to, effects caused by:
  - a) Improper tire inflation and/or improper load/speed practices.
  - b) Improper or insufficient tire rotation.
    - Any tire with premature or irregular wear caused by failing to follow the recommended tire rotation pattern and/or mileage intervals as delineated by this Limited Protection Policy.
    - Wear due to improper vehicle alignment including but not limited to, uneven, cupping, irregular, spotty, and feathering wear.
- Damage due to:
  - a) Rim irregularities or rim damage.
  - b) Snow chains.
  - c) Vehicle mechanical problems, including brake problems, and vehicle wheel alignment.
  - d) Extreme temperature exposure.
  - e) Negligent and abusive driving such as tire spinning, or racing.
  - f) Improper tire storage.
  - g) Automotive accident.
  - h) Chemical corrosion or fire.
  - i) Use contrary to the vehicle manufacturer's tire recommendations.
  - j) Improper stud size and/or installation.
  - k) Improper mounting or demounting. l) Alteration: such as, but not limited to, adding a white inlay on blackwall, tread regrooving, tire truing or siping, or adding sealant materials to the tire.
  - m) Weather checking/cracking: not covered after 24 months from the date of purchase.

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply.

### HERCULES TIRE & RUBBER CO.'S OBLIGATIONS

Replacement of Eligible Tires will be made by any Ironman Tires brand authorized dealer or vehicle dealer authorized to handle Ironman Tires brand tire adjustments ("Authorized Dealer"). Hercules Tire & Rubber Co. will replace the tire pursuant to the terms of this Limited Protection Policy. Tires that are replaced under an adjustment basis under this Limited Protection Policy become the property of Hercules Tire & Rubber Co.

### OWNER'S OBLIGATIONS

To make an eligible claim under this Limited Protection Policy, the owner must present a claim with the tire to an Authorized Dealer. For the nearest Authorized Dealer, consult a local directory, internet search engine, [www.herculestire.com](http://www.herculestire.com), or call 1-844-708-7291. Owner must present an original tire sales invoice indicating the date of purchase. Owner will be required to sign the Ironman Limited Protection Policy Claim Form. Owner is responsible for paying all applicable taxes set forth under this Limited Protection Policy. Owner is also responsible for paying local tire disposal fees and any parts or service regardless of mileage or months of service. This includes payment for tire rotation, alignment, towing, road service, valve stems and tire repair. Owner is responsible for maintaining proper tire air pressure and for proper maintenance of the tire. Owner must rotate tires at least every 6,000 to 8,000 miles (10-13,000 kilometers) or sooner if uneven tread wear begins to appear.

### CONDITIONS AND EXCLUSIONS

The Limited Protection Policy described herein applies only to tires purchased in the United States or Canada. No representative, agent or employee of Hercules Tire & Rubber Co. or its dealers has any authority to make any representation,

# LIMITED PROTECTION POLICY

## IRONMAN® TIRES LIMITED PROTECTION POLICY

promise, agreement or change to this Limited Protection Policy except as specifically stated herein. Passenger Tires purchased prior to six years before the date you present them for adjustment are excluded.

### PASSENGER CAR TIRES

Ironman Tires passenger car tires which become unserviceable because of the following conditions are excluded from Limited Protection Policy coverage and are not subject to adjustment: tires run flat, underinflated or overloaded (refer to information molded on tire sidewalls and vehicle manufacturer's recommended load tables), tires worn unevenly or rapidly due to misalignment, improper mounting or other mechanical irregularity, repairable punctures, tires misused or abused, vandalism, loss from fire, wreck or collision, tires used in other than normal passenger car service (normal passenger car service includes tires used in normal passenger car service by the original owner in the furtherance of his trade or business but excludes the use of the tire in truck, racing, off the highway service, campers, emergency response vehicles or on vehicles which are leased or for hire, including taxis, limousines or similar vehicles), tires concerning which recommended maintenance has not been performed by the user.

### LIGHT TRUCK TIRES

Ironman Tires light truck tires removed from service because of the following conditions are excluded from this Limited Protection Policy coverage and are not subject to adjustment: cuts, snags, punctures, tires run flat or underinflated, tires worn unevenly or rapidly due to misalignment, improper mounting or other mechanical irregularity, tires misused or abused, vandalism, loss from fire, wreck or collision, tires used in other than normal service including improper load and inflation (refer to information molded on tire sidewalls and vehicle manufacturer's recommended load tables), tires concerning which recommended maintenance has not been performed by the user.

### USAGE OF PRODUCT

This Limited Protection Policy applies only to tires which are equivalent in size and load range rating to the size and load range rating recommended by the manufacturer of the vehicle on which the tires are mounted and operated in accordance with the vehicle manufacturer's recommendations.

### GENERAL

All tire adjustments under this Limited Protection Policy are CONTINGENT upon:

- a. Completion of the Registration and Limited Protection Policy forms at the time of sale.
- b. The subject tire not having been mounted on any other vehicle than on that on which it was first mounted.
- c. The claim being presented by the original purchaser of the subject tire.
- d. Copy of original invoice. You must also present personal identification (e.g., driver's license) and vehicle registration upon request and must make the vehicle on which the tires were mounted available for inspection.

No adjustment pursuant to this Limited Protection Policy shall in any way be determined or construed as an admission or indication on the part of Hercules Tire & Rubber Co. or on any other party that any tire or tube adjusted or determined to be adjustable is in fact either defective in workmanship and/or material, or poor or merchantable quality or in any way unfit for the use for which it was intended, or serve to set a precedent for any further adjustment. This Limited Protection Policy specifically excludes and does not cover you for any loss of time, loss of use of the vehicle, or any incidental or consequential damages relating to the quality, condition or performance of the product. Some states and provinces do not allow the exclusion or limitation of incidental or consequential damages so the above exclusion may not apply to you.

HERCULES TIRE & RUBBER COMPANY RESERVES THE RIGHT TO THE FINAL INSPECTION DECISION FOR ALL RETURNED TIRES. THIS LIMITED PROTECTION POLICY IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. HERCULES EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, WARRANTIES

OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SOME U.S. STATES AND/OR CANADIAN PROVINCES DO NOT ALLOW LIMITATIONS ON THE DURATION OF AN IMPLIED PROTECTION, SO THE ABOVE MAY NOT APPLY TO YOU. TO THE EXTENT PERMITTED BY LAW, HERCULES DISCLAIMS LIABILITY FOR ALL CONSEQUENTIAL AND INCIDENTAL DAMAGES. THE REMEDIES SET FORTH IN THIS LIMITED PROTECTION POLICY ARE THE SOLE AND EXCLUSIVE REMEDIES FOR BREACH OF PROTECTION POLICY. SOME U.S. STATES AND/OR CANADIAN PROVINCES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS LIMITED PROTECTION POLICY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM U.S. STATE TO STATE OR CANADIAN PROVINCE TO PROVINCE. THIS IS THE ONLY EXPRESSED PROTECTION POLICY MADE BY HERCULES. NO HERCULES EMPLOYEE, RETAILER, OR DEALER HAS THE AUTHORITY TO MAKE ANY PROTECTION POLICY, PROTECTION REPRESENTATION, PROMISE OR AGREEMENT ON BEHALF OF HERCULES EXCEPT AS EXPRESSLY WRITTEN IN THIS LIMITED PROTECTION POLICY IN OBSERVANCE OF U.S. FEDERAL LAW, THIS LIMITED PROTECTION POLICY HAS BEEN DESIGNATED A "LIMITED PROTECTION POLICY." HERCULES DOES NOT INTEND TO REPRESENT THROUGH THIS LIMITED PROTECTION POLICY THAT TIRE FAILURES CAN OR CANNOT HAPPEN.

### ARBITRATION CLAUSE

ALL CLAIMS ARISING OUT OF THIS LIMITED PROTECTION POLICY OR THE MARKETING, SALE OR PERFORMANCE OF THE PURCHASED TIRE(S) AGAINST HERCULES TIRE & RUBBER CO., ITS SUPPLIERS, DEALERS OR ANY OF THEIR AFFILIATES OR ANY OF THEIR AGENTS, EMPLOYEES, OFFICERS OR DIRECTORS (collectively for the purposes of this paragraph "Hercules") SHALL BE SUBJECT TO BINDING ARBITRATION.

You acknowledge that your agreement to subject any claim described above means that you waive and forego any rights you may otherwise have to litigate your claim in a court of law and that you freely choose to resolve any such claim by arbitration upon election of arbitration by you or by Hercules. You agree further that no claim described above shall be litigated or arbitrated as a class action or on a class wide or representative basis or on behalf of the general public. You agree that any judgment or award of the arbitrator(s) will be final and not subject to judicial review. You recognize and agree that the arbitrator(s) shall have no authority to award punitive or other damages not measured by the prevailing party's actual damages, except as may be specifically required by statute.

### ADJUSTMENT POLICY

If found adjustable, an Ironman Tires dealer will promptly replace the tire with a tire of like quality, and the replacement charge will be determined by multiplying the consumer's original purchase price (as verified by consumer's invoice) or at the selling price established by the adjusting dealer by the percentage of original tread depth worn from the tire (the original purchase price does not include local, state taxes or Federal Excise Tax). Hercules Tire & Rubber Co. may, at its option, make a proportionate refund in lieu of replacing an adjustment tire. ANY ADDITIONAL CHARGES FOR LOCAL TAXES, MOUNTING, BALANCING, OR A HIGHER PRICED TIRE ACCEPTED AS A REPLACEMENT SHALL BE PAID BY THE CONSUMER. Should any problem develop in obtaining your replacement tire, you are requested to contact the Consumer Relations Department, telephone 1-844-708-7291.

### ADJUSTMENT PROCEDURES

Unserviceable Ironman brand tires adjustable under the terms of this Limited Protection Policy should be returned to an Ironman Tires dealer. To locate an Ironman Tires dealer:

- a. See "Find a Dealer" at [ironmantires.com](http://ironmantires.com)
- b. Call Ironman Tires at 1-844-708-7291

# ALL-STEEL PROTECTION POLICY

## IRONMAN ALL-STEEL MEDIUM TRUCK, LIGHT TRUCK AND SPECIALTY TRAILER TIRE LIMITED PROTECTION POLICY

### WHO IS ELIGIBLE?

You are eligible for the benefits of this Limited Protection Policy if:

- You are the owner of new Ironman brand all-steel medium truck tires.
- Your tires bear Department of Transportation-prescribed tire identification numbers and are not "NA" (not adjustable) or "blem" (cosmetically blemished).
- Your Ironman all-steel medium truck tires have been used only on the vehicle on which they were originally installed according to the vehicle manufacturer's or tire manufacturer's recommendations.

### WHAT IS COVERED, AND FOR HOW LONG?

Free Tire Replacement – Ironman brand all-steel medium truck tires covered by this Limited Protection Policy that become unserviceable due to a defect in workmanship or material during first 2/32nds of an inch of usable treadwear or three (3) months from date of purchase, whichever comes first, will be replaced with a comparable new Ironman tire without charge. You pay only for the mounting, balancing and full F.E.T. or T.S.F. (Without proof of purchase, date of manufacture will be used to determine age.)

Prorated Tire Replacement – Tires worn beyond the first 2/32nds of usable tread, or more than three (3) months from date of purchase, whichever comes first, that become unserviceable due to a defect in workmanship or material will be replaced on a prorated basis. You are responsible for mounting, balancing and full F.E.T. or T.S.F.

### HOW WILL PRORATED CHARGES BE CALCULATED?

The replacement price will be calculated using the current Ironman selling price and multiplying by the percentage of original useable tread (that is remaining at the time of replacement).

### WHAT IS A COMPARABLE TIRE?

A "comparable" new Ironman tire may either be the same line of tire or, in the event that the tire is not available, a tire of the same basic construction and quality with a different sidewall or tread design. If a higher-priced tire is accepted as replacement, the difference in price will be at an additional charge to you. Any replacement tire provided pursuant to this Limited Protection Policy will be covered by the new Ironman all-steel tire Limited Protection Policy in effect at the time of replacement.

### WHAT IS NOT COVERED BY THIS LIMITED PROTECTION POLICY?

- Tires branded or marked "NA" (not adjustable) or "blem" (cosmetically blemished), or that have been previously adjusted.
- Irregular wear or tire damage due to:
  - Road Hazards (including punctures, cuts, snags, impact breaks, etc.).
  - Wreck, collision, fire, or vandalism.
  - Improper inflation, overloading, misapplication, misuse, negligence, high-speed tire spinning, chain damage, improper mounting or demounting.
  - Mechanical condition of the vehicle, including misalignment, wheel imbalance, or faulty shocks or brakes.
- Ride disturbance after the first 2/32nds of treadwear or due to damaged wheels or any vehicle condition.
- Ozone or weather cracking on tires over five (5) years from date of manufacture.
- Alteration of the tire or addition of alien material or transfer from one vehicle to another.
- Loss of time or use inconvenience, or any incidental or consequential damages.
- Failure due to improper or faulty tube.
- Tires used for racing.

### WHEN DOES THE LIMITED PROTECTION POLICY END?

A tire has delivered its full original treadlife and the new tire coverage of this Limited Protection Policy ends when the treadwear indicators become visible, or five (5) years from the date of original tire manufacture or new tire purchase date (without proof of purchase, date of manufacture will be used to determine age), whichever comes first.

### HOW DO YOU OBTAIN AN ADJUSTMENT?

In order to be eligible for Ironman Limited Protection Policy service, the owner must:

- Present the tire to an authorized Ironman Tires retailer, and
- Present proof of purchase (if applicable to faction of the retailer), and
- Complete and sign an Ironman Limited Protection Policy Claim Form, which is available at any authorized dealer, and
- Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges, or cost of other services ordered.

Contact your authorized Ironman Tires dealer for Limited Protection Policy information and procedures.

### DISCLAIMER

This Limited Protection Policy, or any protection policy stated or referred to herein, is exclusive and in lieu of any other guarantee regarding the quality of Ironman Tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein.

# CASING PROTECTION

## CASING LIMITED PROTECTION POLICY

### WHAT IS COVERED AND FOR HOW LONG?

Ironman brand all-steel medium truck tires are covered when the tire becomes unserviceable or non-retreadable due to a defect in workmanship or material. A predetermined casing allowance will be provided.

The Casing Limited Protection Policy is valid during the first retreaded life or for five (5) years from the date of manufacture, whichever comes first.

### WHAT IS NOT COVERED BY THIS LIMITED PROTECTION POLICY?

Tires used in mining and logging service are not covered under this Limited Protection Policy.

Size(s)	
215/75R17.5, 235/75R17.5, 245/70R17.5	\$ 30.00
225/70R19.5, 245/70R19.5, 265/70R19.5	\$ 30.00
8.25R15	\$ 20.00
10.00R15	\$ 20.00
8R19.5	\$ 10.00
10.00R20	\$ 50.00
9R22.5, 10R22.5	\$ 50.00
255/70R22.5, 275/70R22.5	\$ 65.00
295/75R22.5, 275/80R22.5, 295/80R22.5, 315/80R22.5	\$ 90.00
385/65R22.5, 425/65R22.5, 445/65R22.5	\$100.00
11R22.5, 12R22.5	\$ 90.00
12.00R24	–
285/75R24.5	\$ 90.00
11R24.5	\$ 90.00

### WHEN DOES THE LIMITED PROTECTION POLICY END?

A tire has delivered its full original tread life and the new tire coverage of this Limited Protection Policy ends when the treadwear indicators become visible, or five (5) years from the date of the original tire manufacture or new tire purchase date (without proof of purchase, date of manufacture will be used to determine age), whichever comes first. Casings may continue to be covered under the Limited Protection Policy beyond the new tire coverage.

### HOW DO YOU OBTAIN AN ADJUSTMENT?

In order to be eligible for Ironman Limited Protection Policy service, you must:

- Present the adjusted tire to an authorized Ironman retailer, and
- Present proof of purchase (if applicable) to the retailer, and
- Complete and sign an Ironman Limited Protection Policy Claim Form, which is available at any authorized dealer, and
- Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges, or cost of other services ordered.

Contact your authorized Ironman Tires dealer for Limited Protection Policy information and procedures.

### DISCLAIMER

This Limited Protection Policy, or any protection policy stated or referred to herein, is exclusive and in lieu of any other guarantee regarding the quality of Ironman Tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein. Casing Limited Protection Policy valid only in North America.



## ROAD HAZARD PROTECTION POLICY

This Road Hazard coverage is offered upon the purchase of select new Ironman branded SUV/PMetric/Light Truck and passenger tire purchased in the United States or Canada. This protection policy is valid from the date of purchase for two (2) years or when the tire reaches 50% of usable tread depth, whichever comes first. When an eligible tire is damaged during the first 2/32nds of an inch (1.6mm) of treadwear or first 12 months from date of purchase, whichever came first, the tire will be replaced with a comparable Ironman brand tire free of charge. After the first 2/32nds up to the 50% of usable tread depth within the two (2) years coverage, credit is prorated.

- If an Ironman tire is removed after the covered period no credit will be issued.
- Applicable taxes on the new tire and costs of mounting and balancing shall be borne by consumer.
- When the tire has 2/32nds of an inch or less in tread depth, it is considered worn out.
- The Road Hazard Protection is effective on tires purchased on or after July 1st, 2019.

### ROAD HAZARD EXCLUSIONS:

This Road Hazard protection policy excludes Ironman Tires Medium Truck tires. All exclusions described under the section of "What is not covered" within this Limited Protection Policy and other exclusions include, but are not limited to, effects caused by:

1. A tire that is damaged/failed due to vandalism.
2. A tire that is damaged/failed due to an accident.
3. A tire that is damaged/failed due to commercial, industrial or agricultural use.
4. A tire that is damaged/failed due to racing.
5. A tire that is damaged/failed due to off-road use.
6. A tire that is damaged/failed due to snow chains or studs.
7. A tire that is damaged/failed due to rapid or irregular wear.
8. A tire that is damaged/failed due to wear from worn mechanical components on the vehicle.
9. Tires transferred from the vehicle on which they were originally installed.
10. Loss of time, inconvenience, loss of use of vehicle or consequential damage.
11. Any tires used on any emergency response vehicle.
12. Repairable under USTMA guidelines.
13. Tires that reflect damage due to continued run flat or acute under-inflation.
14. Tire series 40 and lower (i.e. 40,35,30,25 and 20)

SUMMARY OF APPLICABLE TREAD PATTERN		
Category	Pattern	Road Hazard
PASSENGER	iMOVE <sup>™</sup> Gen3 AS	YES
	iMOVE <sup>™</sup> Gen2 AS	YES
	iMOVE <sup>™</sup> PT	YES
	RB-12	YES
	RB-12 NWS	YES
	GR906	YES
	Polar Trax GEN2	NO
SUV/LIGHT TRUCK	iMOVE <sup>™</sup> GEN2 SUV	YES
	RB-SUV & RB-LT	YES
	Radial A/P	YES
	All Country <sup>™</sup> AT2	YES
	All Country <sup>™</sup> A/T	YES
	All Country <sup>™</sup> M/T	NO
	All Country <sup>™</sup> CHT	YES
	All Country <sup>™</sup> HT	YES
	I-109 LT	NO

Tire Size	Tread Design	Buff Radius		Maximum Buff Width	
		IN	MM	IN	MM
11R22.5	I-109 EcoFT	17.7	450	8.7	220
11R22.5	I-208 EcoFT	18.5	470	8.7	220
11R22.5	I-301	17.7	450	8.7	220
11R22.5	I-370 EcoFT	18.5	470	8.7	220
11R22.5	I-460 EcoFT	19.7	500	8.7	220
11R22.5	I-480	19.7	500	8.7	220
11R22.5	I-502	21.7	550	8.7	220
11R22.5	I-601 EcoFT	17.7	450	8.7	220
11R24.5	I-109 EcoFT	17.7	450	8.7	220
11R24.5	I-208 EcoFT	18.5	470	8.7	220
11R24.5	I-301	17.7	450	8.7	220
11R24.5	I-370 EcoFT	18.5	470	8.7	220
11R24.5	I-502	21.7	550	8.7	220
11R24.5	I-601 EcoFT	17.7	450	8.7	220
11R24.5	I-480	19.7	500	8.7	220
12.00R24	I-301	31.8	809	9.2	234
215/75R17.5	I-109	19.5	496	6.7	170
225/70R19.5	I-109	20.0	507	6.9	176
225/70R19.5	I-604	15.4	390	7.1	180
225/70R22.5	I-181	23.6	600	8.5	215
235/75R17.5	I-109	23.1	587	7.6	194
245/70R19.5	I-109	16.7	425	8.0	202
245/70R19.5	I-604	19.1	485	8.0	204
285/75R24.5	I-109 EcoFT	23.6	600	8.9	225
285/75R24.5	I-208 EcoFT	23.6	600	8.9	225
285/75R24.5	I-370 EcoFT	23.6	600	8.9	225
285/75R24.5	I-480	23.6	600	8.9	225
285/75R24.5	I-502	23.6	600	8.9	225
285/75R24.5	I-601 EcoFT	23.6	600	8.9	225
295/75R22.5	I-109 EcoFT	24.6	625	9.4	240
295/75R22.5	I-208 EcoFT	24.6	625	9.4	240
295/75R22.5	I-460 EcoFT	29.5	750	9.4	240
295/75R22.5	I-480	20.9	530	9.1	230
295/75R22.5	I-502	27.6	700	9.4	240
295/75R22.5	I-601 EcoFT	24.6	625	9.4	240
295/75R22.6	I-370 EcoFT	29.5	750	9.4	240
315/80R22.5	I-301	25.6	650	10.2	260
315/80R22.5	I-402	37.4	950	9.8	250
315/80R22.5	I-502	37.4	950	9.8	250
385/65R22.5	I-402	39.4	1000	12.6	320
425/65R22.5	I-402	43.3	1100	13.6	345
445/65R22.5	I-402	46.5	1180	14.8	375
7.50R16 Tubeless	I-109	15.4	392	6.7	170
425/65R22.5	I-402	43.3	1100	13.6	345
445/65R22.5	I-402	46.5	1180	14.8	375
285/75R24.5	I-109 EcoFT	23.6	600	8.9	225
285/75R24.5	I-208 EcoFT	23.6	600	8.9	225
285/75R24.5	I-370 EcoFT	23.6	600	8.9	225
285/75R24.5	I-480	23.6	600	8.9	225
285/75R24.5	I-502 EcoFt	23.6	600	8.9	225
285/75R24.5	I-601 EcoFT	23.6	600	8.9	225
7.50R16 Tubeless	I-109LT	15.4	392	6.7	170





12200 Herbert Wayne Court, Suite 150 · Huntersville, NC 28078  
844-432-9729 · [www.ironmantires.com](http://www.ironmantires.com)



  
**IRONMAN**™  
TIRES TO TRUST